EVERLIGHT AMERICAS

DATASHEET

SMD ▪ Full Color Top View LEDs
EAPL3528WA0

PRELIMINARY



Features

- P-LCC-4 package.
- White package.
- Optical indicator.
- Colorless clear window.
- Ideal for backlight and light pipe application.
- Inter reflector.
- Wide viewing angle.
- Suitable for vapor-phase reflow.
- Computable with automatic placement equipment.
- Available on tape and reel (8mm Tape).
- Pb-free.
- The product itself will remain within RoHS compliant version.
- Precondition: Bases on JEDEC J-STD 020D Level 3

Description

The 67-22 series is available in soft red, green,blue and yellow. Due to the package design, the LED has wide viewing angle and optimized light coupling by inter reflector. This feature makes the ideal for light pipe application. The low current requirement makes this device ideal for portable equipment or any other application where power is at a premium.

Applications

- Telecommunication: indicator and backlighting in telephone and fax.
- Flat backlight for LCD's, switches and symbols.
- Light pipe application.
- General use.

Copyright © 2010, Everlight Americas Inc. All Rights Reserved. Release Date : 30.04.2014. Issue No: 1

Device Selection Guide

Chip Materials	Emitted Color	Resin Color
InGaN	Pure White	Yellowish

Absolute Maximum Ratings (Ta=25℃)

Parameter	Symbol	Rating	Unit
Reverse Voltage	V_R	5	V
Forward Current	I_F	30	mA
Peak Forward Current (Duty 1/10 @1KHz)	I_{FP}	100	mA
Power Dissipation	Pd	110	mW
Junction Temperature	T_j	115	℃
Operating Temperature	T_{opr}	-40 ~ +85	℃
Storage Temperature	Tstg	-40 ~ +90	℃
Thermal Resistance	Rth $_{J-A}$	600	K/W
	Rth $_{J-S}$	400	K/W
ESD (Classification acc. AEC Q101)	ESD_{HBM}	2000	V
	ESD_{MM}	200	V
Soldering Temperature	T_{sol}	Reflow Soldering : 260 ℃ for 10 sec. Hand Soldering : 350 ℃ for 3 sec.	

Copyright © 2010, Everlight Americas Inc. All Rights Reserved. Release Date : 30.04.2014. Issue No: 1

Electro-Optical Characteristics (Ta=25℃)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Iv	3600	-----	7200	mcd	I_F=20mA
Viewing Angle	$2\theta_{1/2}$	-----	120	-----	deg	I_F=20mA
Forward Voltage	V_F	2.9	----	3.6	V	I_F=20mA
Reverse Current	I_R	-----	-----	50	μA	V_R=5V

Note:
1. Tolerance of Luminous Intensity: ±11%
2. Tolerance of Forward Voltage: ±0.1V
3. For each die.

Bin Range of Luminous Intensity

Bin Code	Min.	Max.	Unit	Condition
Y2	3600	4500	mcd	I_F =20mA
Z01	4500	5700		
Z02	5700	7200		

Note:
Tolerance of Luminous Intensity: ±11%

Bin Range of Forward Voltage

Bin Code	Min.	Max.	Unit	Condition
36	2.9	3.0	V	I_F =20mA
37	3.0	3.1		
38	3.1	3.2		
39	3.2	3.3		
40	3.3	3.4		
41	3.4	3.5		
42	3.5	3.6		

Note:
Tolerance of Forward Voltage: ±0.1V


Copyright © 2010, Everlight Americas Inc. All Rights Reserved. Release Date : 30.04.2014. Issue No: 1

Bin Range of Chromaticity Coordinate

Bin Code	CIE_x	CIE_y	Unit	Condition
A0	0.280	0.248	nm	I_F =20mA
	0.264	0.267		
	0.283	0.305		
	0.296	0.276		
B3	0.287	0.295		
	0.283	0.305		
	0.304	0.330		
	0.307	0.315		
B4	0.307	0.315		
	0.304	0.330		
	0.330	0.360		
	0.330	0.339		
B5	0.296	0.276		
	0.287	0.295		
	0.307	0.315		
	0.311	0.294		
B6	0.311	0.294		
	0.307	0.315		
	0.330	0.339		
	0.330	0.318		

Note:
1.Tolerance of Chromaticity Coordinates: ±0.01
2.For each die.


The C.I.E. 1931 Chromaticity Diagram




Copyright © 2010, Everlight Americas Inc. All Rights Reserved. Release Date : 30.04.2014. Issue No: 1

Typical Electro-Optical Characteristics Curves


Spectrum Distribution




Forward Current vs. Forward Voltage




Relative Luminous Intensity vs. Ambient Temperature




Relative Luminous Intensity vs Forward Current



Forward Current Derating Curve




Radiation Diagram



Copyright © 2010, Everlight Americas Inc. All Rights Reserved. Release Date : 30.04.2014. Issue No: 1

Package Dimension



Note: Tolerances unless mentioned ±0.1mm. Unit = mm

Copyright © 2010, Everlight Americas Inc. All Rights Reserved. Release Date : 30.04.2014. Issue No: 1


Moisture Resistant Packing Materials

Label Explanation




- CPN: Customer's Product Number
- P/N: Product Number
- QTY: Packing Quantity
- CAT: Luminous Intensity Rank
- HUE: Dom. Wavelength Rank
- REF: Forward Voltage Rank
- LOT No: Lot Number

Reel Dimensions




Carrier Tape Dimensions: Loaded Quantity 2000 pcs Per Reel



Note: Tolerances unless mentioned ±0.1mm. Unit = mm

Copyright © 2010, Everlight Americas Inc. All Rights Reserved. Release Date : 30.04.2014. Issue No: 1

Moisture Resistant Packing Process




Note: Tolerances unless mentioned ±0.1mm. Unit = mm

Precautions for Use

1. Over-current-proof

1.1 Customer must apply resistors for protection, otherwise slight voltage shift will cause big current change (Burn out will happen).



2. Storage

2.1 Moisture proof bag should only be opened immediately prior to usage.

2.2 Environment should be less than 30℃ and 60% RH when moisture proof bag is opened.

2.3 After opening the package MSL Conditions stated on page 1 of this spec should not be exceeded.

2.4 If the moisture sensitivity card indicates higher than acceptable moisture, the component should be baked at min. 60deg +/-5deg for 24 hours.

3. Soldering Condition

3.1 Pb-free solder temperature profile

3.2 Reflow soldering should not be done more than two times.

3.3 When soldering, do not put stress on the LEDs during heating.

3.4 After soldering, do not warp the circuit board.

4. Soldering Iron

Each terminal is to go to the tip of soldering iron temperature less than 350℃ for 3 seconds within once in less

Copyright © 2010, Everlight Americas Inc. All Rights Reserved. Release Date : 30.04.2014. Issue No: 1

than the soldering iron capacity 25W. Leave two seconds and more intervals, and do soldering of each terminal. Be careful because the damage of the product is often started at the time of the hand solder.

5. Repairing

Repair should not be done after the LEDs have been soldered. When repairing is unavoidable, a double-head soldering iron should be used (as below figure). It should be confirmed beforehand whether the characteristics of the LEDs will or will not be damaged by repairing.

Application Restrictions

High reliability applications such as military/aerospace, automotive safety/security systems, and medical equipment may require different product. If you have any concerns, please contact Everlight before using this product in your application. This specification guarantees the quality and performance of the product as an individual component. Do not use this product beyond the specification described in this document.

Revision History

Rev.	Modified date	File modified contents
1	2014/4/30	New Spec

Copyright © 2010, Everlight Americas Inc. All Rights Reserved. Release Date : 30.04.2014. Issue No: 1