

Power Supplies

- Mini Redundant Power

PS300-HRP

| | | | | | | | |
|---|--------------------------------------|------------------------|-----------------|-----------------|------|------|------------------|
| Model Name | P/N: 50914709620E | | | | | | |
| PS300-HRP Redundant Power ATX 300W | Input Range | 90 ~ 264Vac Full Range | | | | | |
| | Output Voltage | +5V | +3.3V | +12V | -12V | -5V | +5Vsb |
| | | 25A (3A min) | 18A (1A min) | 16A (2A min) | 0.5A | 0.5A | 2A (0.1A min) |
| | MTBF (hours) | 100,000h | | | | | |
| | Safety | UL, UL+C, TUV, CB, CE | | | | | |
| | Dimensions | 185 x 150 x 86 mm | | | | | |
| | Compatible with Axiomtek Products | AX61220/AX6156LE | | | | | |



Overview

Embedded
Systems

Embedded
Systems for
Transportation

Embedded
Field
Controllers

Embedded
MicroBoxes

Industrial
Barebone
Systems

Industrial
Chassis

Backplanes

Power
Supplies

Peripherals &
Accessories

PS400-HRP

| | | | | | | | |
|---|--------------------------------------|------------------------|-----------------|-----------------|------|------|------------------|
| Model Name | P/N: 50914B09620E | | | | | | |
| PS400-HRP Redundant Power ATX 400W | Input Range | 90 ~ 264Vac Full Range | | | | | |
| | Output Voltage | +5V | +3.3V | +12V | -12V | -5V | +5Vsb |
| | | 35A (3A min) | 25A (1A min) | 28A (2A min) | 1.2A | 0.5A | 2A (0.1A min) |
| | MTBF (hours) | 100,000h | | | | | |
| | Safety | UL, UL+C, TUV, CB, CE | | | | | |
| | Dimensions | 185 x 150 x 86 mm | | | | | |
| | Compatible with Axiomtek Products | AX6156LE/AX61220 | | | | | |



PS501-HRP (AC inlet in front)

| | | | | | | | |
|--|--------------------------------------|---------------------------|-------|------|------|-------|--|
| Model Name | P/N: 50904C09010E | | | | | | |
| PS501-HRP Redundant Power ATX500W | Input Range | 100 ~ 240Vac Full Range | | | | | |
| | Output Voltage | +5V | +3.3V | +12V | -12V | +5Vsb | |
| | | 25A | 25A | 41A | 0.8A | 3.5A | |
| | MTBF (hours) | AT 25°C 100,000h | | | | | |
| | Safety | CB, CCC, UL, TUV, CE, FCC | | | | | |
| | Dimensions | 185 x 150 x 86 mm | | | | | |
| | Compatible with Axiomtek Products | AX6156LE/AX61220 | | | | | |



Power Supplies

- Mini Redundant Power

PS500-HRP

| | | | | | | |
|---|--------------------------------------|---|-----------------|-----------------|------|--------------------|
| Model Name | P/N: 50904C09000E | | | | | |
| PS500-HRP Redundant Power ATX 500W | Input Range | 100 ~ 240Vac Full Range | | | | |
| | Output Voltage | +5V | +3.3V | +12V | -12V | +5Vsb |
| | | 25A (1A min) | 25A (1A min) | 41A (1A min) | 0.8A | 3.5A (0.1A min) |
| | MTBF (hours) | AT 25°C 100,000h | | | | |
| | Safety | UL, TUV, CB, CCC, RFI/EMI Standards, FCC Class B, CISPR22 Class B | | | | |
| | Dimensions | 185 x 150 x 86 mm | | | | |
| | Compatible with Axiomtek Products | AX61492 | | | | |

