Ordering number: EN4768

SANYO

No.4768

2SC4922

NPN Epitaxial Planar Silicon Transistor

Muting Circuit, Driver Applications

Features

- High DC current gain.
- On-chip bias resistance (R1 = 47kΩ, R2 = 47kΩ)
- Very small-sized package permitting 2SC4922-applied sets to be made smaller and slimmer.
- Small ON resistance.

Absolute Maximum Ratings at Ta = 25°C

			unit
Collector-to-Base Voltage	V_{CBO}	25	V
Collector-to-Emitter Voltage	V_{CEO}	20	V
Emitter-to-Base Voltage	V_{EBO}	10	V
Input Voltage	V_{IN}	18	V
Collector Current	I_C	100	mA
Collector Current (Pulse)	I_{CP}	200	mA
Base Current	I_B	20	mA
Collector Dissipation	P_C	150	mW
Junction Temperature	Tj	150	°C
Storage Temperature	Tstg	−55 to +150	°C


Electrical Characteristics at Ta = 25°C

			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	V_{CB} = 20V, I_E = 0			0.1	μA
Collector Cutoff Current	I_{CEO}	V_{CE} = 15V, I_B = 0			0.5	μA
Emitter Cutoff Current	I_{EBO}	V_{EB} = 5V, I_C = 0	30	53	80	μA
DC Current Gain	h_{FE}	V_{CE} = 2V, I_C = 5mA	200			
Gain-Bandwidth Product	f_T*	V_{CE} = 5V, I_C = 10mA		240		MHz
Output Capacitance	Cob*	V_{CB} = 10V, f = 1MHz		1.4		pF
C-E Saturation Voltage	$V_{CE(sat)}$	I_C = 2mA, I_B = 0.2mA		10	30	mV
C-B Breakdown Voltage	$V_{(BR)CBO}$	I_C = 10μA, I_E = 0	25			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	I_C = 1mA, R_{BE} = ∞	20			V
Input OFF-State Voltage	$V_{I(off)}$	V_{CE} = 2V, I_C = 100μA	0.7	1.0	1.4	V
Input ON-State Voltage	$V_{I(on)}$	V_{CE} = 0.3V, I_C = 5mA	1.0	1.5	3.0	V
Input Resistance	R1		32	47	62	kΩ
Resistance Ratio	R1/R2		0.9	1.0	1.1	
ON Resistance	Ron	V_{IN} = 10V, f = 1MHz		4.0		Ω

* Characteristic of the constituent transistor.


Marking : GA

Electrical Connection



Package Dimensions 2106A

(unit : mm)




1 : Base
2 : Emitter
3 : Collector


SANYO : SMCP

SANYO Electric Co., Ltd. Semiconductor Business Headquarters
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN


h_{FE} – I_C




I_C – $V_{I(off)}$




$V_{I(on)}$ – I_C



Ron – V_{IN}



P_C – Ta



■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:
① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.