
SAW Bandpass Filter 202155B

1. Features

- IF Bandpass Filter
- High Attenuation
- Single-Ended Operation
- DIP Package
- Maximum Storage Temperature Range : -40℃ ~ 85℃
- Electrostatics Sensitive Device (ESD)

2. Package Dimension



Package : D2512

Dimensions shown are nominal in millimeters

Base : Fe(SPCC), Au plating over Ni plated
Cap : Cu & Cr Alloy, Ni Plated
Termination : Kovar, Au Plated

Pin Configuration	
1	Input
5	Output
2, 4	Ground
3, 6	Case ground

3. Specifications

Fo = 70.0 MHz

Terminating source impedance : 50Ω and matching network

Terminating load impedance : 50Ω and matching network


		Minimum	Typical	Maximum
Center Frequency	MHz	69.93	70.0	70.07
Insertion Loss	dB	-	23.0	25.0
1dB Bandwidth	MHz	-	6.5	-
3dB Bandwidth	MHz	6.7	6.84	-
40dB Bandwidth	MHz	-	8.1	8.25
Amplitude Ripple (Fo +/- 3.0 MHz)	dB	-	0.7	1.0
Group Delay Variation (Fo +/- 3.0 MHz)	nsec	-	90	150
Absolute Delay	usec	-	9.09	-
Ultimate Rejection	dB	50	55	-
Temperature Coefficient of Frequency	ppm/°C	-	-94	-

Notes :

1) All specifications are based on the matching schematic shown below
2) All specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature
3) All attenuation measurements are measured relative to insertion loss

4. Matching Schematic

(Actual matching values may vary due to PCB layout and parasitics)



L1 = 56 nH

5. Marking Configuration

ITF[1] 04A001[2]


202155B[3]


1) Manufacturer name

2) Lot Number


3) Part Number


6. Typical Performance (at +25℃)







SAW Bandpass Filter 202155B









Integrated Technology Future	**I T F Co., Ltd.** 102-901, Bucheon Technopark 364, Samjeong-Dong, Ojeong-Gu, Bucheon-City, Gyounggi-Do, Korea 421-809	Part No.	202155B
		Rev. Date	2004-04-21
		Rev.	NI1013- CS03 5/5