

**SPECIFICATIONS**

**USB TYPE C Connector**

**Mechanical**

**Mating Force:** 5~20 N max.  
**Unmating Force:** 8~20 N up to 1,000 mating cycles,  
 6~20 N after 1,000 durability cycles.  
**Durability:** 10,000 cycles.


**USB TYPE C Series**  
**Right Angle, Hybrid, 24**  
**Pos.**

**Electrical**


**Voltage Rating:** 30 V rms maximum.  
**Low Level Contact Resistance:** 40 mΩ maximum initial for the Power (VBUS), Ground (GND) and others contacts ;  
 50 mΩ maximum after environment test.  
**Dielectric Withstanding Voltage:** 100V AC (Rms.).  
**Insulation Resistance:** 100MΩ min. at 100V DC.

**Physical**

**Housing:** Thermoplastic, UL 94V-0 rated in Black color  
**Contact and Shell:** Copper alloy & stainless steel  
**Plating:** See "ORDERING INFORMATION"  
**Operating Temperature:** -20°C to +85°C



**DRAWING**



**ORDERING INFORMATION**

PRODUCT NO.: UT 1 1 1 1 C - 1 34 0F - 7 H

Series Prefix	Halogen Free
USB 3.1 TYPE C	Package Code
Termination Type	7: Tape & Reel
1: Right Angle, Hybrid SMT & T/H.	Extension Code
Position	Center Height
1: 24 POS.	34: 3.40 mm
CONFIGURATION	HSG Color+Shell Plating
1: Single, Top-mount	1: Black HSG+Ni Plating
Contact Area Plating	
C: 30u" Pd/Ni+GOLD FLASH	