

Specifications

Parameter		Unit	Minimum	Typical	Maximum
Center Frequency		MHz	-	600	-
Insertion Loss(f0±20MHz)		dB	-	23	24
1.5 dB Bandwidth		MHz	40	46.97	-
3 dB Bandwidth		MHz	45	48.5	-
35 dB Bandwidth		MHz	-	55.88	60
Passband Variation(f0±20MHz)		dB	-	1.4	2
Absolute Delay		usec	-	0.64	-
Group Delay Variation(f0±20MHz)		nsec	-	30	150
Ultimate Rejection	100 ~570MHz	dB	30	25	-
	630 ~650MHz	dB	30	30	-
	650 ~1000MHz	dB	30	35	-
Material Temperature coefficient		KHz/°C	-49.2		
Ambient Temperature		°C	25		
Package Size		SMD7.0*5.0			

Notes:

1. All specifications are based on the test circuit shown
2. In production, devices will be tested at room temperature to a guardbanded specification to ensure electrical compliance over temperature
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
4. This is the optimum impedance in order to achieve the performance show

Matching Configuration

INPUT
50 Ω



OUTPUT
50 Ω

Source / Load Impedance = 50 ohm


Notes - Component values may change depending
on board layout.



SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060

Part Number	SP60001		
Rev. Date	2007-05-06		
Ver.	1.0	Page	1/4

Package Dimension



- 1) ∴ Pad Number 1 Index
- 2) SIPAT: Manufacturer name
- 3) SP60001: Part Number
- 4) 07XX: Date Code

Input	9
Output	4
Ground	1,2,3,5,6,7,8,10


Package: SMD7.0*5.0

Unit: mm

	SIPAT Co., Ltd. (CETC No. 26 Research Institute) Nanping Huayuan Road No. 14 Chongqing, China, 400060	Part Number	SP60001	
		Rev. Date	2007-05-06	
		Ver.	1.0	Page 2/4


Typical Performance

Frequency Response




Horizontal: 20MHz/Div Vertical: 10dB/Div

Passband Response




Horizontal: 10MHz/Div Vertical: 0.5dB/Div

Group Delay Variation($f_0 \pm 20\text{MHz}$)




Horizontal: 10MHz/Div Vertical: 20ns/Div

Phase Linearity($f_0 \pm 20\text{MHz}$)




Horizontal: 10MHz/Div Vertical: 10deg/Div

Smith Chart S11



Smith Chart S22



SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060

Part Number

SP60001

Rev. Date

2007-05-06

Ver.

1.0

Page 3/4

Maximum Ratings

Operating Temperature Range	°C	[-40°C;+85°C]
Storage Temperature Range	°C	[-40°C;+105°C]
DC Voltage	V	0
Input Power	dBm	10 max
ESD Class		1



SIPAT Co., Ltd.
(CETC No. 26 Research Institute)
Nanping Huayuan Road No. 14
Chongqing, China, 400060

Part Number	SP60001		
Rev. Date	2007-05-06		
Ver.	1.0	Page	4/4