
SIPMOS® Small-Signal-Transistor

Features


- P-Channel
- Enhancement mode
- Avalanche rated
- d*v*/d*t* rated
- Pb-free lead finishing; RoHS compliant

Product Summary

V_{DS}	-60	V
$R_{DS(on),max}$	0.3	Ω
I_D	-1.9	A



PG-SOT-223



Type	Package	Tape and reel information	Marking	Lead free	Packing
BSP 170 P	PG-SOT-223	L6327: 1000pcs/reel	BSP170	Yes	Non Dry

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
			steady state	
Continuous drain current	I_D	T_A=25 °C	-1.9	A
		T_A=70 °C	-1.5	
Pulsed drain current	$I_{D,pulse}$	T_A=25 °C	-7.6	
Avalanche energy, single pulse	E_{AS}	I_D=1.9 A, R_{GS}=25 Ω	70	mJ
Avalanche energy, periodic limited by T_{jmax}	E_{AR}		0.18	
Reverse diode d*v*/d*t*	d*v*/d*t*	I_D=1.9 A, V_{DS}=48 V, d*i*/d*t*=-200 A/µs, $T_{j,max}$=150 °C	-6	kV/µs
Gate source voltage	V_{GS}		±20	V
Power dissipation	P_{tot}	T_A=25 °C	1.8	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 150	°C
ESD class		JESD22-A114 (HBM)	1A (250V to 500V)	
Soldering temperature			260 °C	
IEC climatic category; DIN IEC 68-1			55/150/56	


Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics						
Thermal resistance, junction -soldering point	R_{thJS}		-	-	20	K/W
SMD version, device on PCB:	R_{thJA}	minimal footprint	-	-	110	K/W
		6 cm^2 cooling area[1)]	-	-	70	
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0 V, I_D=-250 µA	-60	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=-250 µA	-2.1	-3	-4	
Zero gate voltage drain current	I_{DSS}	V_{DS}=-60 V, V_{GS}=0 V, T_j=25 °C	-	-0.1	-1	µA
		V_{DS}=-60 V, V_{GS}=0 V, T_j=125 °C	-	-10	-100	
Gate-source leakage current	I_{GSS}	V_{GS}=-20 V, V_{DS}=0 V	-	-10	-100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=-10 V, I_D=-1.9 A	-	239	300	mΩ
Transconductance	g_{fs}	$\|V_{DS}\|>2\|I_D\|R_{DS(on)max}$, I_D=-1.9 A	1.3	2.6	-	S

[1)] Device on 40mm*40mm*1.5 epoxy PCB FR4 with 6cm^2 (one layer, 70µm thick) copper area for drain connection. PCB is vertical without blown air.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=-25 V, f=1 MHz	-	328	410	pF
Output capacitance	C_{oss}		-	105	135	
Reverse transfer capacitance	C_{rss}		-	38	48	
Turn-on delay time	$t_{d(on)}$	V_{DD}=-30 V, V_{GS}=-10 V, I_D=-1.9 A, R_G=6 Ω	-	14	21	ns
Rise time	t_r		-	28	42	
Turn-off delay time	$t_{d(off)}$		-	92	138	
Fall time	t_f		-	60	90	
Gate Charge Characteristics						
Gate to source charge	Q_{gs}	V_{DD}=-48 V, I_D=-1.9 A, V_{GS}=0 to -10 V	-	-1.4	-1.9	nC
Gate to drain charge	Q_{gd}		-	-4.9	-7.4	
Gate charge total	Q_g		-	-10	-14	
Gate plateau voltage	$V_{plateau}$		-	-4.34	-	V
Reverse Diode						
Diode continuous forward current	I_S	T_A=25 °C	-	-	-1.98	A
Diode pulse current	$I_{S,pulse}$		-	-	-7.6	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=-1.9 A, T_j=25 °C	-	-0.83	-1.1	V
Reverse recovery time	t_{rr}	V_R=30 V, I_F=$\|I_S\|$, di_F/dt=100 A/µs	-	36	54	ns
Reverse recovery charge	Q_{rr}		-	41	62	nC


1 Power dissipation

$P_{tot}=f(T_A)$



2 Drain current


$I_D=f(T_A)$; $|V_{GS}|\geq 10$ V



3 Safe operating area

$I_D=f(V_{DS})$; $T_A=25$ °C[1)]; $D=0$


parameter: t_p



4 Max. transient thermal impedance

$Z_{thJA}=f(t_p)$


parameter: $D=t_p/T$



5 Typ. output characteristics

I_D=f(V_{DS}); T_j=25 °C


parameter: V_{GS}



6 Typ. drain-source on resistance

$R_{DS(on)}$=f(I_D); T_j=25 °C


parameter: V_{GS}



7 Typ. transfer characteristics


I_D=f(V_{GS}); $|V_{DS}|>2|I_D|R_{DS(on)max}$

parameter: T_j




8 Typ. forward transconductance

g_{fs}=f(I_D); T_j=25 °C




9 Drain-source on-state resistance

$R_{DS(on)}$=f(T_j); I_D=-1.9 A; V_{GS}=-10 V




10 Typ. gate threshold voltage

$V_{GS(th)}$=f(T_j); V_{GS}=V_{DS}; I_D=-250 µA



11 Typ. capacitances


C=f(V_{DS}); V_{GS}=0 V; f=1 MHz



12 Forward characteristics of reverse diode

I_F=f(V_{SD})


parameter: T_j



13 Avalanche characteristics

I_{AS}=f(t_{AV}); R_{GS}=25 Ω


parameter: $T_{j(start)}$



14 Typ. gate charge


V_{GS}=f(Q_{gate}); I_D=-1.9 A pulsed

parameter: V_{DD}




15 Drain-source breakdown voltage

$V_{BR(DSS)}$=f(T_j); I_D=-250 µA




Package Outline

SOT-223: Outline




Footprint



Packaging

Tape



Dimensions in mm

Published by
Infineon Technologies AG
81726 München, Germany
© Infineon Technologies AG 2006.
All Rights Reserved.

Attention please!
The information given in this data sheet shall in no event be regarded as a guarantee of conditions or characteristics (“Beschaffenheitsgarantie”). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office (**www.infineon.com**).

Warnings
Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.
Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.