



Part No.

# XTXT-HOS-8ft

*Quick-test XT 10,000 psi hose, S.S. hose ends, 8ft long*

10,000 psi (689 bar) working pressure Microbore hoses that provide a very quick, low volume, high pressure way of connecting to any pressure instrumentation, hand pump, calibration source or device under test

## Features

- Low volume reduces the pumping effort or compressed gas usage in pressure calibration
- No thread sealant required – connect to adapters without wrenches, thread sealant or thread tape
- Bubble tight connections to 10000 psi (689 bar) with no moving parts reduces maintenance to almost zero
- Hose is hard to break and very flexible
- Adapt from hose to virtually any device under test with only one connection
- A corrosion resistant strain-relief on each hose end reduces wear and dramatically increases hose life
- Note that these hoses are NOT compatible with QTHA adapters. Please use XTHA adapters
- Made in USA

## Specifications

|                     |   |
|---------------------|---|
| Length              | 8 ft  |
| Pressure Range      | 0 to 10000 psi (0 to 689 bar)   |
| Burst Pressure      | 40000 psi (2,756 bar)   |
| End 1               | Female Quick-test XT, stainless steel                                       |
| End 2               | Female Quick-test XT, stainless steel                                       |
| Temperature range   | -40 to 140 °F (-40 to 60 °C)  |
| Outer Diameter      | 0.24 in (6.1 mm)  |
| Inner Diameter      | 0.08 in (2.0 mm)  |
| Minimum Bend Radius | 1 in (25.4 mm)  |
| Color               | Blue  |
| Construction        | Polyamide core tube, High tensile synthetic fiber and polyamide outer cover |
| End materials       | Stainless Steel   |
| Fluid Media         | Water, Petroleum Based Oil, Air, Inert Gas                                  |