

ONLINE DATA SHEET
www.mysick.com

Photoelectric sensors
W2S-2, Photoelectric proximity sensor, Background suppression

WTB2SC-2P3274



SICK
Sensor Intelligence.

SICK
Sensor Intelligence.

Photoelectric sensors
W2S-2, Photoelectric proximity sensor, Background suppression

Type > WTB2SC-2P3274
Part No. > 1063646





Illustration may differ

At a glance

- Sensing ranges of up to 150 mm
- Almost no black/white shift up to 60 mm
- Sensor with line-shaped light spot
- Sensor with laser-like focused light spots
- Precise background suppression that is immune to interference/crosstalk
- High-performance PinPoint 2.0 LED

Your benefits

- An ultra-compact design with the performance of large photoelectric proximity sensors offers new space-saving machine construction possibilities.
- Large variety of proximity sensors and operating concepts enable a wide range of application options
- Use in confined spaces: detection of small, flat parts thanks to high-quality background suppression and almost nonexistent black/white shift
- Remote access: models with IO-Link allow data to be easily accessed from the PLC
- High availability and long-term use in grippers thanks to flexible and rugged cable entry

IO-Link PinPoint 2.0 by SICK

Features

Sensor/detection principle:	Photoelectric proximity sensor, Background suppression
Dimensions (W x H x D):	7.7 mm x 21.8 mm x 13.5 mm
Housing design (light emission):	Rectangular
Sensing range max.:	4 mm ... 90 mm [1]
Sensing range:	10 mm ... 70 mm [2]
Preset sensing range:	45 mm
Type of light:	Visible red light
Light source:	PinPoint LED [3]
Wave length:	640 nm
Special features:	Line-shaped light spot
Adjustment:	Cable
Light spot size (distance):	2.2 mm x 9 mm (45 mm)
IO-Link functions:	Standard functions

[1] [2] Object with 90 % reflectance (referred to standard white, DIN 5033) [3] Average service life: 100,000 h at T_U = +25 °C

© SICK AG. Subject to change without notice.


Mechanics/electronics

Supply voltage:	10 V DC ... 30 V DC [1]
Ripple:	≤ 5 Vpp [2]
Current consumption:	≤ 20 mA [3]
Output type:	PNP [4]
Switching mode:	Light switching [5]
Switching mode selector:	Programmable
Output current Imax.:	< 50 mA
Response time:	< 0.5 ms [6]
Switching frequency:	1,000 Hz [7]
Connection type:	Cable with M8 male connector, 4-pin, 200 mm [8]
Cable material:	PVC
Cable diameter:	Ø 3 mm
Circuit protection:::	A, B, D [9] [10] [11]
IO-Link:	✓
Special device:	-
Optics material:	PMMA
Enclosure rating:	IP 67
Special feature:	Line-shaped light spot
Description:	IO-Link
Ambient operating temperature:	-25 °C ... +50 °C
Ambient storage temperature:	-40 °C ... +75 °C
UL File No.:	NRKH.E181493
Housing material:	ABS/PC, Plastic
Transmission rate:	COM2

[1] Limit values [2] May not exceed or fall below U_V tolerances [3] Without load [4] [5] Parametrisable via IO-Link [6] Signal transit time with resistive load [7] With light/dark ratio 1:1 in switching mode. Different values possible in IO-Link mode [8] Do not bend below 0 °C [9] A = V_S connections reverse-polarity protected [10] B = output reverse-polarity protected [11] D = outputs overcurrent and short-circuit protected


© SICK AG. Subject to change without notice.

Dimensional drawing




|1| Optical axis, receiver
|2| Optical axis, sender
|3| Middle axis fixing hole Ø 3.2 mm
|4| Status indicator LED green: supply voltage on
|5| Status indicator LED,
yellow: Status of received light beam
|6| Connection

Connection diagram




© SICK AG. Subject to change without notice.

Characteristic curve



|1| Sensing range on white, 90 % remission
|2| Sensing range on gray, 18 % remission
|3| Sensing range on black, 6 % remission

Light spot size




Dimensions in mm (inch)

Sensing range	Spot diameter Vertical	Horizontal
0 (0.00)	3.5 (0.14)	3.8 (0.15)
10 (0.39)	3.0 (0.12)	5.2 (0.20)
20 (0.79)	3.3 (0.13)	6.4 (0.25)
30 (1.18)	1.8 (0.07)	7.4 (0.29)
40 (1.57)	2.0 (0.08)	8.6 (0.34)
60 (2.36)	4.4 (0.17)	10.5 (0.41)
80 (3.15)	6.5 (0.26)	12.8 (0.50)
100 (3.94)	9.0 (0.35)	14.5 (0.57)

© SICK AG. Subject to change without notice.

Sensing range diagram



|1| Sensing range on white, 90 % remission
|2| Sensing range on gray, 18 % remission
|3| Sensing range on black, 6 % remission
|4| Sensing range on ultrablack, 1 % remission

© SICK AG. Subject to change without notice.

A4 4c int43

Australia
Phone +61 3 9457 0600
1800 33 48 02 – tollfree
E-Mail sales@sick.com.au

Belgium/Luxembourg
Phone +32 (0)2 466 55 66
E-Mail info@sick.be

Brasil
Phone +55 11 3215-4900
E-Mail marketing@sick.com.br

Canada
Phone +1 905 771 14 44
E-Mail information@sick.com

Česká republika
Phone +420 2 57 91 18 50
E-Mail sick@sick.cz

China
Phone +86 4000 121 000
E-Mail info.china@sick.net.cn
Phone +852-2153 6300
E-Mail ghk@sick.com.hk

Danmark
Phone +45 45 82 64 00
E-Mail sick@sick.dk

Deutschland
Phone +49 211 5301-301
E-Mail info@sick.de

España
Phone +34 93 480 31 00
E-Mail info@sick.es

France
Phone +33 1 64 62 35 00
E-Mail info@sick.fr

Great Britain
Phone +44 (0)1727 831121
E-Mail info@sick.co.uk

India
Phone +91–22–4033 8333
E-Mail info@sick-india.com

Israel
Phone +972-4-6881000
E-Mail info@sick-sensors.com

Italia
Phone +39 02 27 43 41
E-Mail info@sick.it

Japan
Phone +81 (0)3 5309 2112
E-Mail support@sick.jp

Magyarország
Phone +36 1 371 2680
E-Mail office@sick.hu

Nederland
Phone +31 (0)30 229 25 44
E-Mail info@sick.nl

Norge
Phone +47 67 81 50 00
E-Mail sick@sick.no

Österreich
Phone +43 (0)22 36 62 28 8-0
E-Mail office@sick.at

Polska
Phone +48 22 837 40 50
E-Mail info@sick.pl

România
Phone +40 356 171 120
E-Mail office@sick.ro

Russia
Phone +7-495-775-05-30
E-Mail info@sick.ru

Schweiz
Phone +41 41 619 29 39
E-Mail contact@sick.ch

Singapore
Phone +65 6744 3732
E-Mail sales.gsg@sick.com

Slovenija
Phone +386 (0)1-47 69 990
E-Mail office@sick.si

South Africa
Phone +27 11 472 3733
E-Mail info@sickautomation.co.za

South Korea
Phone +82 2 786 6321/4
E-Mail info@sickkorea.net

Suomi
Phone +358-9-25 15 800
E-Mail sick@sick.fi

Sverige
Phone +46 10 110 10 00
E-Mail info@sick.se

Taiwan
Phone +886 2 2375-6288
E-Mail sales@sick.com.tw

Türkiye
Phone +90 (216) 528 50 00
E-Mail info@sick.com.tr

United Arab Emirates
Phone +971 (0) 4 88 65 878
E-Mail info@sick.ae

USA/México
Phone +1(952) 941-6780
1 (800) 325-7425 – tollfree
E-Mail info@sickusa.com

More representatives and agencies
at **www.sick.com**

SICK
Sensor Intelligence.