



MAPX	MODIFICATION	DATE

- Note:
- Material:
    - Housing: High temperature thermoplastic with g.f,UL94v-0
    - Contact: copper alloy,t=0.20mm
    - Shell: copper alloy,t=0.25mm
  - Specification:
    - Current rating:1,5PIN 1.8A Max/2,3,4PIN 1A Max.
    - Dielectric withstanding voltage: 100 V(ac) for 1 min.
    - Contact resistance: 30 mΩ Max.
    - Insulation resistance: 100 MΩ Min.
    - Total mating force: 3.57 Kgf Max.
    - Total unmating force: 1.0 Kgf Min.
    - Temperature range: -30°C~80°C

RECOMMENDED PCB LAYOUT  
PCB图仅供参考

产品图 PRODUCT CHART DWG		深圳市精拓金电子有限公司							
公差一览表 TOLERANCE UNLESS OTHERWISE		单位 UNITS	MM	制图 DRAWING	YANG	制图料号 PRODUCT PART NO.	920-C52A2021S10112		
.X	$\pm 0.30$	.X	$\pm 5^\circ$	比例 SCALE	1:1	审核 CHKD	郭志富	产品名称 PRODUCT NO.	MICRO 5S B型5.9两脚长1.25插板 有边有柱加焊脚SMT短端
.XX	$\pm 0.25$	.XX	$\pm 2^\circ$	日期 DATE	2019.11.23	核准 APPD	黄国荣	角法 VIEW	
.XXX	$\pm 0.20$	.XX	$\pm 1^\circ$	版本 VER	A0	角法 VIEW		版本 VER	A0