
SSSS9 5(H)mm, 2mm-travel Type

Mid-size general purpose type well established for user friendliness



Typical Specifications

Items		Specifications	
Rating (max.)/(min.) (Resistive load)		0.1A 12V DC / 1mA 5V DC	
Contact resistance (Initial performance / After lifetime)		30mΩ max. / 80mΩ max.	
Operating force		2-position	3-position
		3±1.5N	a, c → b 2±1N b → a, c 3±1.5N
Operating life	Without load	10,000 cycles	
	With load	10,000 cycles (0.1A 12V DC)	

Product Line

Travel (mm)	Actuator direction	Actuator length (mm)	Poles	Positions	Mounting method	Changeover timing	Soldering	Minimum order unit (pcs.) Japan	Minimum order unit (pcs.) Export	Products No.	Drawing No.
2	Vertical	2	1	2	Standard	Non shorting	Manual, Dip	100	5,000	**SSSS912000**	1
					Snap-in (t1.6)					**SSSS910400**	2
				3	Standard	Not specified				**SSSS919500**	3
					Snap-in (t1.6)					**SSSS918500**	4
			2	2	Standard	Non shorting				**SSSS922000**	5
				3		Not specified			4,000	**SSSS921800**	6
		4	1	2		Non shorting			5,000	**SSSS912500**	1
					Snap-in (t1.6)					**SSSS910800**	2
				3	Standard	Not specified				**SSSS919800**	3
					Snap-in (t1.6)					**SSSS918700**	4
			2	2	Standard	Non shorting				**SSSS922500**	5
				3		Not specified			4,000	**SSSS923200**	6
					Snap-in (t1.6)					**SSSS920600**	7
	Horizontal	2	1	2	Standard	Non shorting			5,000	**SSSS916900**	8
					Snap-in (t1.6)					**SSSS915001**	9
				3	Standard	Not specified				**SSSS91B900**	10
			2	2		Non shorting				**SSSS926400**	12
				3		Not specified			4,000	**SSSS928500**	14
		4	1	2		Non shorting			5,000	**SSSS916400**	8
					Snap-in (t1.6)					**SSSS914503**	9
				3	Standard	Not specified				**SSSS91B600**	10
					Snap-in (t1.6)					**SSSS91A601**	11
			2	2	Standard	Non shorting				**SSSS925800**	12
					Snap-in (t1.6)					**SSSS923802**	13
				3	Standard	Not specified			4,000	**SSSS928200**	14
					Snap-in (t1.6)					**SSSS925701**	15

Note

Please contact us for automotive use products.

Refer to P.111 for soldering conditions.

Packing Specifications







Bulk

Products No.	Number of packages (pcs.)		Export package measurements (mm)
	1 case / Japan	1 case / export packing	
SSSS921800, SSSS923200, SSSS920600, SSSS928500, SSSS928200, SSSS925701	800	4,000	400×270×290
SSSS912000, SSSS910800, SSSS926400, SSSS910400, SSSS919800, SSSS916400, SSSS919500, SSSS918700, SSSS914503, SSSS918500, SSSS922500, SSSS91B600, SSSS922000, SSSS916900, SSSS91A601, SSSS912500, SSSS915001, SSSS925800, SSSS91B900, SSSS923802	1,000	5,000	

Dimensions

Vertical Actuator Type









Unit:mm

No.	Style	PC board mounting hole dimensions (Viewed from direction A)
1	**1-pole, 2-position Standard type** 	
2	**1-pole, 2-position Snap-in type** 	
3	**1-pole, 3-position Standard type** 	

Dimensions

Vertical Actuator Type









Unit:mm

No.	Style	PC board mounting hole dimensions (Viewed from direction A)
4	**1-pole, 3-position Snap-in type** 	
5	**2-pole, 2-position Standard type** 	
6	**2-pole, 3-position Standard type** 	
7	**2-pole, 3-position Snap-in type** 	

Dimensions

Horizontal Actuator Type









Unit:mm

No.	Style	PC board mounting hole dimensions (Viewed from direction A)
8	**1-pole, 2-position** **Standard type** 	
9	**1-pole, 2-position** **Snap-in type** 	
10	**1-pole, 3-position** **Standard type** 	
11	**1-pole, 3-position** **Snap-in type** 	

Dimensions


Horizontal Actuator Type

Unit:mm





No.	Style	PC board mounting hole dimensions (Viewed from direction A)
12	**2-pole, 2-position Standard type** 	
13	**2-pole, 2-position Snap-in type** 	
14	**2-pole, 3-position Standard type** 	
15	**2-pole, 3-position Snap-in type** 	

Detail of ⓐ






Unit:mm



Circuit Diagram (Viewed from Direction A)

1-pole, 2-position Drawing No.1, 2, 8, 9	1-pole, 3-position Drawing No.3, 4, 10, 11	2-pole, 2-position Drawing No.5, 12, 13	2-pole, 3-position Drawing No.6, 7, 14, 15
			

List of Varieties


Series			SSSS2※1	SSSS9	SSAC	SSSF※2	SSSU※2
Photo							
Actuator direction	Horizontal		●	●	●	●	●
	Vertical		●	●	—	●	●
Poles-positions	1-2		●	●	—	●	●
	1-3		●	●	—	●	●
	1-4		●	—	—	—	—
	2-2		●	●	●	●	●
	2-3		●	●	●	●	●
	2-4		●	—	—	—	—
	4-2		—	—	—	●	●
Travel (mm)			2	2	1.5	2	3
Operating temperature range			−40℃ to +85℃		−10℃ to +60℃	−40℃ to +85℃	
Automotive use			—	—	—	—	—
Life cycle			★3	★3	★3	★3	★3
Rating (max.) (Resistive load)			0.3A 6V DC	0.1A 12V DC	1mA 5V DC	0.1A 30V DC	
Rating (min.) (Resistive load)			50μA 3V DC	1mA 5V DC	50μA 3V DC	10μA 1V DC	
Durability	Operating life without load		10,000 cycles 100mΩ max.※1	10,000 cycles 60mΩ max.	10,000 cycles 200mΩ max.	10,000 cycles 45mΩ max.	
	Operating life with load Load: as rating		10,000 cycles 130mΩ max.※1	10,000 cycles 80mΩ max.		10,000 cycles 65mΩ max.	
Electrical performance	Initial contact resistance		70mΩ max.	30mΩ max.	100mΩ max.	25mΩ max.	
	Insulation resistance		100MΩ min. 500V DC		100MΩ min. 100V DC	100MΩ min. 500V DC	
	Voltage proof		500V AC for 1minute		100V AC for 1minute	500V AC for 1minute	
Mechanical performance	Terminal strength		3N for 1minute		5N for 1minute		
	Actuator strength	Operating direction	20N	30N	5N	30N	
		Pulling direction	10N				
Environmental performance	Cold		−20℃ 500h	−40℃ 500h	−20℃ 96h	−40℃ 500h	
	Dry heat		85℃ 500h		85℃ 96h	85℃ 500h	
	Damp heat		60℃, 90 to 95%RH 500h		40℃, 90 to 95%RH 96h	60℃, 90 to 95%RH 500h	
Page			90	95	101	103	107

Slide Switches Soldering Conditions · 111
Slide Switches Cautions · 112

Note
1. ※ 1. Operating life for SSSS213202 is 100 cycles.
2. ※ 2. The operating temperature range for automotive applications can be raised upon request. Please contact us for details.
3. ● Indicates applicability to all products in the series.

Example of Reflow Soldering Condition

1. Heating method: Double heating method with infrared heater.
2. Temperature measurement: Thermocouple ϕ 0.1 to 0.2 CA (K) or CC (T) at soldering portion (copper foil surface).
   A heat resisting tape should be used for fixed measurement.
3. Temperature profile



Series (Reflow type)			A (℃) 3s max.	B (℃)	C (s)	D (℃)	E (℃)	F (s)
SSSS2	Vertical	1-pole, 3-position	260	230	40	180	150	120
	Horizontal	1-pole, 2-position 1-pole, 3-position 2-pole, 3-position						
	Vertical	1-pole, 2-position	250					
SSSS7								
SSAH, SSAG, SSAJ, SSAL, SSSS8			260					

Notes

1. The condition mentioned above is the temperature on the mounting surface of a PC board. There are cases where the PC board' s temperature greatly differs from that of the switch, depending on the PC board' s material, size, thickness, etc. The above-stated conditions shall also apply to switch surface temperatures.
2. Soldering conditions differ depending on reflow soldering machines. Prior verification of soldering condition is highly recommended.

Reference for Hand Soldering

Series	Soldering temperature	Soldering time
SSSF, SSSU	350±10℃	3+1/0s
SSSS2	350±10℃	4s max.
SSSS9	350±10℃	3s max.
SSAH, SSAG, SSAJ, SSAL	350±5℃	3s max.
SSSS8	330±5℃	3s max.
SSSS7	320±5℃	3s max.
SSAC	300±10℃	2s max.

Reference for Dip Soldering

(For PC board terminal types)

Series	Items		Dip soldering	
	Preheating temperature	Preheating time	Soldering temperature	Duration of immersion
SSSS2	100℃ max.	60s max.	260±5℃	3±1s
SSSS9	120℃ max.	60s max.	260±5℃	5+0/-1s (2 times)
SSSF, SSSU	100℃ max.	60s max.	260±5℃	10±1s/5±1s
SSAC	100℃ max.	60s max.	260±5℃	5±1s