

## Applications


- Radar



## Product Features

- Frequency Range: 3.1 – 3.6 GHz
- Pout: 50 dBm (at  $P_{IN} = 27$  dBm)
- Power Gain: 23 dB (at  $P_{IN} = 27$  dBm)
- PAE: 51 % CW
- Bias:  $V_D = 30$  V pulsed (PW = 15 ms, DC = 30 %),  $I_{DQ} = 300$  mA,  $V_G = -3$  V Typical
- Package Dimensions: 15.2 x 15.2 x 3.5 mm
- Package base is pure Cu offering superior thermal management

## Functional Block Diagram



## General Description

TriQuint's TGA2813-CP is a packaged high-power S-Band amplifier fabricated on TriQuint's TQGaN25 0.25um GaN on SiC process. Operating from 3.1 to 3.6 GHz, the TGA2813-CP achieves 100 W saturated output power, a power-added efficiency of >50%, and 23 dB power gain.

The TGA2813-CP is packaged in a 10-lead 15x15 mm bolt-down package with a Cu base for superior thermal management. It can support a range of bias voltages and performs well under both short and long pulsed conditions. Both RF ports are internally DC blocked and matched to 50 ohms allowing for simple system integration.

Lead free and RoHS compliant.

Evaluation Boards are available upon request.

## Pin Configuration

Pad No.	Symbol
1, 5	$V_G$
2, 4, 7, 9	GND
3	$RF_{IN}$
6, 10	$V_D$
8	$RF_{OUT}$

## Ordering Information

Part	ECCN	Description
TGA2813-CP	3A001.b.2.a	3.1 – 3.6 GHz, 100 W GaN Power Amplifier

### Absolute Maximum Ratings

Parameter	Value
Drain Voltage ( $V_D$ )	40 V
Gate Voltage Range ( $V_G$ )	-8 to 0 V
Drain Current ( $I_D$ )	10.4 A
Gate Current ( $I_G$ )	-8 to 56 mA
Power Dissipation ( $P_{DISS}$ ), 85°C	202 W
Input Power, CW, 50 $\Omega$ , ( $P_{IN}$ )	30 dBm
Input Power, CW, VSWR 3:1, $V_D = 30$ V, 85 °C, ( $P_{IN}$ )	27 dBm
Channel Temperature ( $T_{CH}$ )	275 °C
Mounting Temperature (30 Seconds)	260 °C
Storage Temperature	-55 to 150 °C

Operation of this device outside the parameter ranges given above may cause permanent damage. These are stress ratings only, and functional operation of the device at these conditions is not implied.

### Recommended Operating Conditions

Parameter	Value
Drain Voltage ( $V_D$ ) Pulsed: PW = 15 ms, DC = 30 %	30 V
Drain Current ( $I_{DQ}$ )	300 mA
Drain Current Under RF Drive ( $I_{D\_DRIVE}$ )	See plots p. 8
Gate Voltage ( $V_G$ )	-3 V (Typ.)
Gate Current Under RF Drive ( $I_{G\_DRIVE}$ )	See plots p. 8
Temperature ( $T_{BASE}$ )	-40 to 85 °C

Electrical specifications are measured at specified test conditions. Specifications are not guaranteed over all recommended operating conditions.

### Electrical Specifications

Test conditions unless otherwise noted: 25 °C,  $V_D = 30$  V (PW = 15 ms, DC = 30 %),  $I_{DQ} = 300$  mA,  $V_G = -3$  V typical.

Parameter	Min	Typical	Max	Units
Operational Frequency Range	3.1		3.6	GHz
Input Return Loss		> 7		dB
Output Return Loss		> 4.5		dB
Output Power (at $P_{IN} = 27$ dBm)		50		dBm
Power Gain (at $P_{IN} = 27$ dBm)		23		dB
Power Added Efficiency (at $P_{in} = 27$ dBm)		51		%
Output Power Temperature Coefficient (constant $V_G$ )		-0.003		dBm/°C




### Thermal and Reliability Information

Parameter	Test Conditions	Value	Units
Thermal Resistance ( $\theta_{JC}$ ) <sup>(1)</sup>	$T_{BASE} = 85^{\circ}\text{C}$ , $V_D = 30\text{ V}$ (PW = 15 ms, DC = 30%)	0.89	$^{\circ}\text{C/W}$
Channel Temperature ( $T_{CH}$ ) (Under RF drive)	At Freq = 3.3 GHz, $P_{IN} = 27\text{ dBm}$ : $I_{DQ} = 300\text{ mA}$ , $I_{D\_Drive} = 7.6\text{ A}$	162	$^{\circ}\text{C}$
Median Lifetime ( $T_M$ )	$P_{OUT} = 50.5\text{ dBm}$ , $P_{DISS} = 86\text{ W}$	8.7E+7	Hrs

Notes:







1. Thermal resistance measured to back of package.

Test Conditions:  $V_D = 40\text{ V}$ ; Failure Criteria = 10% reduction in  $I_{D\_MAX}$






### Typical Performance: Small Signal

Conditions unless otherwise specified:  $V_D = 30\text{ V}$  (PW = 15 ms, DC = 30 %),  $I_{DQ} = 300\text{ mA}$ ,  $V_G = -3\text{ V}$  typical.









### Typical Performance: Small Signal

Conditions unless otherwise specified:  $V_D = 30$  V (PW = 15 ms, DC = 30 %),  $I_{DQ} = 300$  mA,  $V_G = -3$  V typical.









### Typical Performance: Large Signal

Conditions unless otherwise specified:  $V_D = 30\text{ V}$  (PW = 15 ms, DC = 30 %),  $I_{DQ} = 300\text{ mA}$ ,  $V_G = -3\text{ V}$  typical.









Conditions unless otherwise specified:  $V_D = 30\text{ V}$  ( $PW = 15\text{ ms}$ ,  $DC = 30\%$ ),  $I_{DQ} = 300\text{ mA}$ ,  $V_G = -3\text{ V}$  typical.




### Typical Performance: Large Signal

Conditions unless otherwise specified:  $V_D = 30\text{ V}$  (PW = 15 ms, DC = 30 %),  $I_{DQ} = 300\text{ mA}$ ,  $V_G = -3\text{ V}$  typical.





## Applications Information and Pin Layout



### Bias-up Procedure

1. Set I<sub>D</sub> limit to 10 A, I<sub>G</sub> limit to 50 mA
2. Apply -5 V to V<sub>G</sub>
3. Apply +30 V to V<sub>D</sub>; ensure I<sub>DQ</sub> is approx. 0 mA
4. Adjust V<sub>G</sub> until I<sub>DQ</sub> = 300 mA (V<sub>G</sub> ~ -3 V Typ.).
5. Turn on RF supply


### Bias-down Procedure

1. Turn off RF supply
2. Reduce V<sub>G</sub> to -5 V; ensure I<sub>DQ</sub> is approx. 0 mA
3. Set V<sub>D</sub> to 0 V
4. Turn off V<sub>D</sub> supply
5. Turn off V<sub>G</sub> supply

### Pin Description

Pin No.	Symbol	Description
1,5	V <sub>G</sub>	Gate Voltage; Bias network is required; must be biased from both sides; see recommended Application Information above.
3	RF <sub>IN</sub>	Output; matched to 50 Ω; DC blocked
2,4,7,9	GND	Must be grounded on the PCB.
6,10	V <sub>D</sub>	Drain voltage; Bias network is required; must be biased from both sides; see recommended Application Information above.
8	RF <sub>OUT</sub>	Input; matched to 50 Ω; DC blocked

## Evaluation Board



NOTE: Both Top and Bottom Vd and Vg must be biased.


### Bill of Material

Reference Des.	Value	Description	Manuf.	Part Number
C1, C2, C7, C8	0.1 $\mu$ F	Cap, 0603, 50 V, 10%, X7R	Various	
C5, C6	10-47 $\mu$ F	Cap, 1206, 50 V, 20%, X5R (10v is OK)	Various	
R1, R2, R5, R6	10 Ohms	Res, 0402, 50V, 5%	Various	
R3, R4	0 Ohms	Res, 0402, 5% (jumper) required for the above EVB design	Various	

## Assembly Notes

1. Clean the board or module with alcohol. Allow it to dry fully.
2. Nylock screws are recommended for mounting the TGA2813-CP to the board.
3. To improve the thermal and RF performance, we recommend the following:
  - a. Apply thermal compound or 4 mils indium shim between the package and the board.
  - b. Attach a heat sink to the bottom of the board and apply thermal compound or 4 mils indium shim between the heat sink and the board.
4. Apply solder to each pin of the TGA2813-CP.
5. Clean the assembly with alcohol.

## Mechanical Information



Units: inches

Tolerances: unless specified

x.xx = ± 0.01

x.xxx = ± 0.005

Materials:

Base: Copper

Lid: Plastic

All metalized features are gold plated

Part is epoxy sealed

Marking:

2813: Part number

YY: Part Assembly year

WW: Part Assembly week

ZZZ: Serial Number

MXXX: Batch ID

**Product Compliance Information****ESD Sensitivity Ratings**

Caution! ESD-Sensitive Device

ESD Rating: TBD  
Value: TBD  
Test: Human Body Model (HBM)  
Standard: JEDEC Standard JESD22-A114

**MSL Rating**

Level 5A at 260 °C convection reflow.  
The part is rated Moisture Sensitivity Level 5A at 260 °C per  
JEDEC standard IPC/JEDEC J-STD-020.

**ECCN**

US Department of Commerce: 3A001.b.2.a

**Solderability**

Compatible with the latest version of J-STD-020, Lead-free solder, 260°C.

**RoHS Compliance**

This part is compliant with EU 2002/95/EC RoHS directive (Restrictions on the Use of Certain Hazardous Substances in Electrical and Electronic Equipment).

This product also has the following attributes:

- Lead Free
- Halogen Free (Chlorine, Bromine)
- Antimony Free
- TBBP-A (C<sub>15</sub>H<sub>12</sub>Br<sub>4</sub>O<sub>2</sub>) Free
- PFOS Free
- SVHC Free

**Contact Information**

For the latest specifications, additional product information, worldwide sales and distribution locations, and information about TriQuint:

Web: [www.triquint.com](http://www.triquint.com)  
Email: [info-sales@triquint.com](mailto:info-sales@triquint.com)

Tel: +1.972.994.8465  
Fax: +1.972.994.8504

For technical questions and application information: Email: [info-products@triquint.com](mailto:info-products@triquint.com)

**Important Notice**

The information contained herein is believed to be reliable. TriQuint makes no warranties regarding the information contained herein. TriQuint assumes no responsibility or liability whatsoever for any of the information contained herein. TriQuint assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the user. All information contained herein is subject to change without notice. Customers should obtain and verify the latest relevant information before placing orders for TriQuint products. The information contained herein or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

TriQuint products are not warranted or authorized for use as critical components in medical, life-saving, or life-sustaining applications, or other applications where a failure would reasonably be expected to cause severe personal injury or death.