

YA42A3

by Burndy
Catalog ID: YA42A3

Prop 65 Notice

UNINSULATED ALUMINUM COMPRESSION TERMINAL, 1-HOLE DESIGNUL Listed 90° C600 Volts to 35 KV.

Product Details

General

Color Code	Gray
Connector Type	Terminal
Die Index	303
Feature - Barrel Type	Standard
Material	Aluminum
Physical Attribute - Number of Holes	1
Physical Attribute - Tongue Type	Standard
Plated	Y
Plating Type	Tin - Electro Plated
Temperature Rating	194
Trade Name	HYLUG™
UPC	781810637159
UPC 12 Digit	7818106371599

Dimensions

Dimension - D inch	1.36 in
Dimension - L Length Overall mm	135 mm
Dimension - Length Overall inch	5.32 in
Dimension - N inch	0.63 in
Dimension - Pad Width inch	2.14 in
Dimension - Strip Length inch	2 7/8
Dimension - Stud Size inch	5/8
Dimension - Z inch	1.00 in
Physical Attribute - Tongue Angle	Straight

Electrical Ratings

Rating - KVA	35 kV
Rating - Minimum Voltage	600
Voltage - Maximum	35000

Conductor Related

Conductor - Copper Str Size	900 Kcmil AL;600 Kcmil CU

Conductor - Copper Str Size Range	900 Kcmil AL-600 Kcmil CU

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL 486A-486B
Standards - Industry Standards Met	UL 486A-486B
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	3

For further technical assistance, please contact us

BURNDY Headquarters
47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:
8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)