



SUGGESTED PANEL CUTOUT



SCHEMATIC



SPECIFICATIONS

FUNCTION:
 2P1T OFF-ON
 Auto OFF Below Calibration Voltage
 Remote Trip

RATINGS:
 ANSI/UL 508 and CAN/CSA C22.2 No.14 (E195908):
 16A 220-240VAC [cURus]
 2HP 220-240VAC (12A FLA, 72A LRA) [cURus]

CALIBRATION VOLTAGE:
 Use: 230V 60Hz
 Release: 120-160V

ELECTRICAL LIFE:
 6,000 Cycles [cURus]

INGRESS PROTECTION:
 IP55

APPROVALS:



COLORS AND MARKINGS

BEZEL:
 Black

ACTUATOR:
 ON: Green
 OFF: Red

MARKING:
 I/O Vertical (1)

MARKING COLOR:
 White

MATERIALS

UPPER BODY:
 Polyamide 6/6 (PA66)

LOWER BODY:
 Polyamide 6/6 (PA66+G10)

BEZEL:
 Polyamide 6/6 (PA66+G10)

ACTUATORS:
 Polyamide 6/6 (PA66)

MOUNTING EARS:
 Polyamide 6/6 (PA66)

COVER:
 Polyvinyl Chloride (PVC)

CONTACTS:
 Silver Alloy Clad Copper (AgSnO/Cu)

TERMINALS:
 Brass

GASKET:
 Rubber

BODY	A	09/08/07	CAB
COLORS	A	09/08/07	CAB
MATERIALS	A	09/08/07	CAB
SPECIFICATIONS	A	09/08/07	CAB
REFERENCE	REV.	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED.

INITIAL RELEASE	22034	10/28/2015	MW
DESCRIPTION	PCR	DATE	DRAWN BY

DIMENSIONS	INCHES [MILLIMETERS]
GENERAL TOLERANCES	±0.020 [±0.5] / ±1"
SCALE	DRAWING NOT TO SCALE
PROJECTION	First Angle

KJD17-22413-112	
ITEM NUMBER	34-KJD1722413112
DATE	10/28/2015
REVISION	A