



1201-23-9

REVISIONS	
ISSUE	CHANGES
0	ER 35804 KH 09/14/94
1	ER 36939 A KH 04/23/96
C	ER 34758 COL 09/06/11

CUSTOMER
SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1
APPROX SURFACE AREA
USED ON

CAGE CODE:91836

JACK, PANEL, N

DRAWN	JCA	DATE	04/27/94
DESIGN	JT	DATE	04/28/92
APPR.		DATE	

WINCHESTER
Electronics
62 Berran Industrial
Road North
Wallingford, CT 06492
B
SIZ

1201-23-9

- NOTES:
1. FOR USE WITH BOEING BMS13-65 OH & ADAMS RUSSELL FC28Z CABLES.
 2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
 3. FOR CRIMPING USE DIE K1H-2212.
 4. INTERFACE PER MIL-STD-348, FIG. 304-2.
 5. FOR USE WITH .22 MAX. PANEL.
 6. CENTER CONTACT (1-534-95MA9) SUPPLIED UNASSEMBLED.
 7. MARK PACKAGE: KINGS 1201-23-9
XX XX (DATE CODE)
 8. MATERIALS:
INSULATOR: TEFLON, ASTM-D-1710
K-GRP SLEEVE: COM. BRONZE, ASTM-B135
CENTER CONTACT: BER. COP., ASTM-B196
ALL OTHER PARTS: BRASS, ASTM-B16

9. FINISHES:
CENTER CONTACTS: .000050 MIN GOLD PER ASTM B488 OVER .000050 MIN NICKEL PER AMS-QQ-N-290(ROHS)
ALL OTHER METAL PARTS: .000050 MIN NICKEL PLATE PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734(ROHS)
10. ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS
VOLTAGE RATING: 1000 VRMS
FREQUENCY RANGE: DC TO 11 GHZ
11. WEIGHT:40.3 GRAMS(0.089 POUNDS)