Low Voltage, 1 Ω Single SPDT Analog Switch (1:2 Multiplexer) with Power Down Protection

DESCRIPTION

The DG4157 is a high performance single pole double throw analog switch designed for 1.65 V to 5.5 V operation with single power rail.

Fabricated with high density CMOS technology, the device achieves low on resistance as 1 Ω at 4.5 V power supply and fast switching speed. The - 3 dB bandwidth is typically 117 MHz.

The DG4157 features break before make switch performance, and guarantees logic high control input threshold as low as 1.4 V over the range up to 5.5 V.

It can handle both analog and digital signals and permits signals with amplitudes of up to V_{CC} to be transmitted in either direction.

Power down protection circuit is built in to prevent abnormal current path through signal pins during power down condition.

Each output pin (A, B_0, or B_1) can withstand greater than 8 kV (human body model).

It is available in both SC-70-6 and miniQFN6 packages.

The features make it an ideal part for the switching of audio, video, and data stream.

FEATURES

- Direct cross of industry standard xxx4157
- 1.65 V to 5.5 V operation voltage range
- Guaranteed 1.4 V logic high input threshold at V_{CC} = 5.5 V
- 117 MHz, - 3 dB bandwidth
- Low on-resistance
- Power down protection
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912


Pb-free Available

RoHS COMPLIANT


HALOGEN FREE

FUNCTIONAL BLOCK DIAGRAM AND PIN CONFIGURATION

SC-70-6L




Top View




Device Marking: G0xx
xx = Date/Lot Traceability Code

miniQFN-6L



Top View



Device Marking: Fx
x = Date/Lot Traceability Code

TRUTH TABLE	
LOGIC INPUT (S)	FUNCTION
0	B_0 Connected to A
1	B_1 Connected to A

ORDERING INFORMATION		
TEMP. RANGE	PACKAGE	PART NUMBER
-40 °C to +85 °C	SC-70-6L	DG4157DL-T1-E3
	miniQFN-6L	DG4157DN-T1-E4

For technical questions, contact: analogswitchtechsupport@vishay.com

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

ABSOLUTE MAXIMUM RATINGS

PARAMETER		LIMIT	UNIT
Reference V+ to GND		-0.3 to +6	V
S, A, B [a]		-0.3 to (V+ + 0.3)	
Continuous Current (Any terminal)		± 200	mA
Peak Current (Pulsed at 1 ms, 10 % duty cycle)		± 400	
Storage Temperature	D Suffix	-65 to +150	°C
Power Dissipation (Packages) [b]	SC-70-6L [c]	250	mW
	miniQFN-6L [d]	160	

Notes

a. Signals on A, or B or S exceeding V+ will be clamped by internal diodes. Limit forward diode current to maximum current ratings.
b. All leads welded or soldered to PC board.
c. Derate 3.1 mW/°C above 70 °C.
d. Derate 2 mW/°C above 70 °C.

SPECIFICATIONS

PARAMETER	SYMBOL	TEST CONDITIONS UNLESS OTHERWISE SPECIFIED V+ = 3 V, V_{IN} = 0 V or V+ [e]	TEMP.[a]	LIMITS -40 °C to +85 °C MIN. [b]	TYP. [c]	MAX. [b]	UNIT
DC Characteristics							
On Resistance	R_{ON}	V+ = 2.7 V, B_0 or B_1 = 1.5 V, I_O = 100 mA	Room	-	1.7	2.5	Ω
			Full	-	-	3	
		V+ = 4.5 V, B_0 or B_1 = 3.5 V, I_O = 100 mA	Room	-	0.95	1.2	
			Full	-	-	1.4	
On Resistance Flatness	$R_{FLATNESS}$	V+ = 2.7 V, B_0 or B_1 = 0.75 V, 1.5 V, I_O = 100 mA	Room	-	0.2	-	
		V+ = 4.5 V, B_0 or B_1 = 1 V, 3.5 V, I_O = 100 mA	Room	-	0.14	0.3	
			Full	-	-	0.4	
On Resistance Match	ΔR_{ON}	V+ = 2.7 V, B_0 or B_1 = 1.5 V, I_O = 100 mA	Room	-	0.04	-	
		V+ = 4.5 V, B_0 or B_1 = 3.5 V, I_O = 100 mA	Room	-	0.05	0.12	
			Full	-	-	0.15	
Switch Off Leakage Current	I_{OFF}	V+ = 5.5 V, A = 1 V, 4.5 V B_0 or B_1 = 4.5 V, 1 V or floating	Room	-2	-	2	nA
			Full	-20	-	20	
Switch On Leakage Current	I_{ON}		Room	-4	-	4	
			Full	-40	-	40	
Digital Control							
Input, High Voltage	V_{INH}	V+ = 2.7 V to 5.5 V	Full	1.4	-	-	V
Input, Low Voltage	V_{INL}		Full	-	-	0.4	
Input Current	I_{INH}, I_{INL}	V_{IN} = 0 or V+	Full	-1	-	1	µA
Power Supply							
Power Supply Range	V+		Full	1.65	-	5.5	V
Quiescent Supply Current	I+	V+ = 5.5 V, V_{IN} = 0 V, 5.5 V	Room	-	0.05	0.5	µA
			Full	-	-	1	

For technical questions, contact: analogswitchtechsupport@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

SPECIFICATIONS

PARAMETER	SYMBOL	TEST CONDITIONS UNLESS OTHERWISE SPECIFIED V+ = 3 V, V_{IN} = 0 V or V+ [e]	TEMP.[a]	LIMITS -40 °C to +85 °C MIN. [b]	TYP. [c]	MAX. [b]	UNIT
AC Characteristics							
Turn-On Time [d]	t_{ON}	V+ = 2.7 V, B_0 or B_1 = 1.5 V, R_L = 50 Ω, C_L = 35 pF	Room	-	40	55	ns
			Full	-	-	60	
		V+ = 4.5 V, B_0 or B_1 = 1.5 V, R_L = 50 Ω, C_L = 35 pF	Room	-	22	37	
			Full	-	-	40	
Turn-Off Time [d]	t_{OFF}	V+ = 2.7 V, B_0 or B_1 = 1.5 V, R_L = 50 Ω, C_L = 35 pF	Room	-	12	27	
			Full	-	-	30	
		V+ = 4.5 V, B_0 or B_1 = 1.5 V, R_L = 50 Ω, C_L = 35 pF	Room	-	8	23	
			Full	-	-	25	
Break-Before-Make Time [d]	t_{BBM}	V+ = 2.7 V, B_0 = B_1 = 1.5 V, R_L = 50 Ω, C_L = 35 pF	Room	1	26	-	
		V+ = 4.5 V, B_0 = B_1 = 1.5 V, R_L = 50 Ω, C_L = 35 pF		1	15	-	
Charge Injection [d]	Q	C_L = 1 nF, R_{GEN} = 0 Ω, V_{GEN} = 0 V	Room	-	50	-	pC
Off Isolation [d]	OIRR	R_L= 50 Ω, f = 1 MHz	Room	-	-58	-	dB
		R_L= 50 Ω, f = 10 MHz		-	-31	-	
Crosstalk [d]	X_{TALK}	R_L= 50 Ω, C_L = 5 pF, f = 1 MHz	Room	-	-63	-	
		R_L= 50 Ω, C_L = 5 pF, f = 10 MHz		-	-36	-	
Bandwidth [d]	BW	R_L= 50 Ω	Room	-	117	-	MHz
Total Harmonic Distortion [d]	THD	R_L= 600 Ω, V_{IN} = 0.5 V, f = 20 kHz to 20 kHz	Room	-	0.02	-	%
Capacitance							
BX Port Off Capacitance [d]	$C_{B(OFF)}$	R_L= 50 Ω, C_L = 5 pF, f = 1 MHz	Room	-	20	-	pF
A Port On Capacitance [d]	$C_{A(ON)}$			-	57	-	
Control Pin Capacitance [d]	C_{IN}			-	5	-	


Notes

a. Room = 25 °C, Full = as determined by the operating suffix.
b. The algebraic convention whereby the most negative value is a minimum and the most positive a maximum, is used in this data sheet.
c. Typical values are for design aid only, not guaranteed nor subject to production testing.
d. Guarantee by design, nor subjected to production test.
e. V_{IN} = input voltage to perform proper function.


Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

For technical questions, contact: analogswitchtechsupport@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)




R_{ON} vs. V_A and Supply Voltage




R_{ON} vs. V_A and Supply Voltage




Supply Current vs. Temperature



R_{ON} vs. V_D and Temperature




Leakage vs. Analog Voltage




Leakage Current vs. Temperature

For technical questions, contact: analogswitchtechsupport@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


TYPICAL CHARACTERISTICS (T_A = 25 °C, unless otherwise noted)




Charge Injection vs. Analog Voltage




Insertion Loss vs. Frequency



Switching Time vs. Temperature



Switching Threshold vs. Supply Voltage



Off-Isolation and Crosstalk vs. Frequency

For technical questions, contact: analogswitchtechsupport@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

TEST CIRCUITS




Fig. 1 - Switching Time




Fig. 2 - Break-Before-Make Interval




Fig. 3 - Charge Injection

For technical questions, contact: analogswitchtechsupport@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000

TEST CIRCUITS




Fig. 4 - Off-Isolation





Fig. 5 - Channel Off/On Capacitance

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?68800.

For technical questions, contact: analogswitchtechsupport@vishay.com
THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. THE PRODUCTS DESCRIBED HEREIN AND THIS DOCUMENT ARE SUBJECT TO SPECIFIC DISCLAIMERS, SET FORTH AT www.vishay.com/doc?91000


SC-70: 6-LEADS



Dim	MILLIMETERS			INCHES		
	Min	Nom	Max	Min	Nom	Max
A	0.90	–	1.10	0.035	–	0.043
A_1	–	–	0.10	–	–	0.004
A_2	0.80	–	1.00	0.031	–	0.039
b	0.15	–	0.30	0.006	–	0.012
c	0.10	–	0.25	0.004	–	0.010
D	1.80	2.00	2.20	0.071	0.079	0.087
E	1.80	2.10	2.40	0.071	0.083	0.094
E_1	1.15	1.25	1.35	0.045	0.049	0.053
e	0.65BSC			0.026BSC		
e_1	1.20	1.30	1.40	0.047	0.051	0.055
L	0.10	0.20	0.30	0.004	0.008	0.012
α	7°Nom			7°Nom		

ECN: S-03946—Rev. B, 09-Jul-01
DWG: 5550


MINI QFN-6L CASE OUTLINE



DIM	MILLIMETERS			INCHES		
	MIN.	NAM.	MAX.	MIN.	NAM.	MAX.
A	0.50	0.55	0.60	0.0197	0.0217	0.0236
A1	0.00	-	0.05	0.000	-	0.002
b	0.15	0.20	0.25	0.006	0.008	0.010
c	0.15 REF			0.006 REF		
D	1.15	1.20	1.25	0.045	0.047	0.049
E	0.95	1.00	1.05	0.037	0.039	0.041
e	0.40 BSC			0.016 BSC		
L	0.30	0.35	0.40	0.012	0.014	0.016
L1	0.40	0.45	0.50	0.016	0.018	0.020

ECN T-07039-Rev. A, 12-Feb-07
DWG: 5958

RECOMMENDED MINIMUM PADS FOR MINI QFN 6L



Mounting Footprint
Dimensions in mm

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

© 2017 VISHAY INTERTECHNOLOGY, INC. ALL RIGHTS RESERVED