



Circular Plug Connectors IP68 Circular Plug Connectors AC 169 kompakt

AC 169 RBU/ 5 DALI blue

Socket, 5 pole, Voltage Rating: 450 V, Current Rating: 17.5 A, Cross-Section: 1.5 mm²

Order Info

Reference Number (ref. no.)	795015D3
PU	200

Type

Type	Socket
Number of poles	5 pole
Clamping Units per Pole	1
Colour	blue
Cross-Section	1.5 mm ²
Connection Type	Screw
PE Function	yes
Protection Against Incorrect Plugging	yes

Technical Data

Voltage Rating	450 V
Current Rating	17.5 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	0.75 mm ²
Core Cross-Section max.	2.5 mm ²
Impulse Voltage Rating	4.0 kV
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
IP Code	IP68
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	6.0 mm
Dismantling Length PE	30.0 mm
Dismantling Length	25.0 mm
Assembly Contact Screw	0.5x3.0 / ⚙ 0.2 Nm
Assembly Strain Relief	⚙ 2.5 Nm
Cable Diameter min.	7.0 mm

Cable Diameter max.	13.5 mm
----------------------------	---------
