



FIBER-OPTIC SENSORS AND FIBERS



## LL3-TV07 | LL3 FIBER-OPTIC SENSORS AND FIBERS



### **Ordering information**

Туре	Part no.
LL3-TV07	5322548
Other medels and appropriate the wave sigk some (1) 2	

Other models and accessories → www.sick.com/LL3

### Detailed technical data

#### Features Fibers **Device type Detection principle** Through-beam system GLL170(T), WLL180T, WLL24 Ex For fiber-optic sensor **Fiber length** 2 m Fiber material Polymethylmethacrylat (PMMA) Jacket material Polyethylen (PE) Fiber head material Polyamid (PA) Outer diameter, fiber-optic cable connec-2.2 mm tion **/**<sup>1)</sup> Fiber-optic cable cuttable Thread size Μ4 Fiber-optic head design Threaded sleeve, 90° deflection Bend radius, fibre-optic cable 2 mm Angle of dispersion < 60° Yes Compatibility with infrared light (1,450 nm) No -40 °C ... +70 °C Ambient operating temperature Application High flexible (static) Highly flexible/elastic fibers (bend radius Yes 1-4 mm) Adapter end sleeves required No Angle of dispersion 14.81° Integrated lens Yes **Minimal object diameter** $0.4 \text{ mm}^{2)}$ Special features 90° deflection integrated, maximum sensing range Included with delivery Mounting, 2 x M4 hexagon nut, FC fiber cutter (5304141) No **Compatibility tip adapters**

 $^{(1)}$  FC fiber optic cable cutter included in delivery.

 $^{2)}$  Minimum detectable object was determined at optimum measuring distance and optimum setting.

#### Classifications

ECI@ss 5.0	27270905
ECI@ss 5.1.4	27270905


ECI@ss 6.0	27270905
ECI@ss 6.2	27270905
ECI@ss 7.0	27270905
ECI@ss 8.0	27270905
ECI@ss 8.1	27270905
ECI@ss 9.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
UNSPSC 16.0901	39121528
Sensing ranges with WLL180T	
Operating mode 16 µs	340 mm
Operating mode 70 µs	1,000 mm
Operating mode 250 µs	1,800 mm
Operating mode 2 ms	4,000 mm
Operating mode 8 ms	4,000 mm
Sensing ranges with GLL170	
Operating mode 250 µs	460 mm

## Sensing ranges with GLL170T

Operating mode 50 µs	840 mm
Operating mode 250 µs	1,290 mm

# Dimensional drawing (Dimensions in mm (inch))

### LL3-TV05, LL3-TV06, LL3-TV07



# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

