This document was generated on 06/06/2017

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 5054334081
Status: Active
Overview: Micro-Lock Plus Wire-to-Board Connector System
Description: Micro-Lock™ PLUS Vertical Header, 1.25mm Pitch, Dual Row, Tin-Bismuth Plating, with Pick-and-Place Polyimide Tape, 40 Circuits, Black



Series image - Reference only

Documents:

Drawing (PDF)
Product Specification 5054320000-002 (PDF)
Application Specification AS-505432-001-001 (PDF)
Application Specification AS-505432-002-001 (PDF)
Packaging Specification 5054339200-200 (PDF)
RoHS Certificate of Compliance (PDF)
Product Literature (PDF)

Agency Certification	
UL	E29179
General	
Product Family	PCB Headers
Series	505433
Application	Signal, Wire-to-Board
Overview	Micro-Lock Plus Wire-to-Board Connector System
Product Literature Order No	987651-4888
Product Name	Micro-Lock™ PLUS
UPC	889056620246
Physical	
Breakaway	No
Circuits (Loaded)	40
Circuits (maximum)	40
Color - Resin	Black
Durability (mating cycles max)	30
First Mate / Last Break	No
Glow-Wire Compliant	No
Guide to Mating Part	Yes
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Tin-Bismuth
Material - Plating Termination	Tin-Bismuth
Material - Resin	Polyamide
Net Weight	1961.942/mg
Number of Rows	2
Orientation	Vertical
PCB Locator	No
PCB Retention	Yes
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface	1.25mm
Pitch - Termination Interface	1.25mm
Plating min - Mating	1.000µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Stackable	No
Surface Mount Compatible (SMC)	Yes
Temperature Range - Operating	-40°C to +105°C
Termination Interface: Style	Surface Mount
Electrical	
Current - Maximum per Contact	1.5A

EU ELV
Not Relevant

EU RoHS
Compliant

China RoHS

REACH SVHC
Not Contained Per -ED/01/2017 (12 January 2017)

Halogen-Free Status
Not Low-Halogen

Need more information on product environmental compliance?

Email productcompliance@molex.com
Please visit the Contact Us section for any non-product compliance questions.

China ROHS	Green Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series
505433 Series

Mates With
Micro-Lock™ PLUS Receptacle Housing
505432

Voltage - Maximum	50V AC (RMS)/DC

Material Info

Reference - Drawing Numbers

Application Specification	AS-505432-001-001, AS-505432-002-001
Packaging Specification	5054339200-200
Product Specification	5054320000-002
Sales Drawing	5054330000-000, 5054331000-000

This document was generated on 06/06/2017

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION