
MH300RW Series

Wide Input, 3W Ultra-Miniature DC/DC Converters



Key Features:

- 3W Output Power
- Miniature 0.55 x 0.55" Case
- Wide 2:1 Input Range
- EN 60950 Approval
- 1,500 VDC Isolation
- >3.45 MHour MTBF
- -40°C to +80°C Operation
- 28 Standard Models

Electrical Specifications

Specifications typical @ +25°C, nominal input voltage & rated output current, unless otherwise noted. Specifications subject to change without notice.

Input

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Start Voltage	5 VDC Input			4.5	VDC
	12 VDC Input			9.0	
	24 VDC Input			18.0	
	48 VDC Input			36.0	
Short Circuit Input Power				0.50	W
Input Filter	Internal Capacitor				

Output

Parameter	Conditions	Min.	Typ.	Max.	Units
Output Voltage Accuracy				±1.5	%
Output Voltage Balance	Dual Output, Balanced Loads			±2.0	%
Line Regulation	VIN = MIN to MAX			±0.2	%
Load Regulation	IOUT = 0% to 100%			±1.0	%
Cross Regulation	See Note 2			±5.0	
Ripple & Noise (20 MHz)	See Note 3		70		mV P - P
Temperature Coefficient			±0.01	±0.02	%/°C
Transient Recovery Time	See Note 4		250	500	µSec
Transient Response Deviation			±3.0	±5.0	%
Overload Protection	See Note 5		170		%
Output Short Circuit	Continuous (Autorecovery)				

General

Parameter	Conditions	Min.	Typ.	Max.	Units
Isolation Voltage	60 Seconds	1,500			VDC
	1 Second	1,800			
Isolation Resistance	500 VDC	1,000			MΩ
Isolation Capacitance	100 kHz, 1.0V		100		pF
Switching Frequency		100			kHz

EMI Characteristics

Parameter	Standard	Criterea	Level
Radiated Emissions	EN 55022		Class A
Conducted Emissions	EN 55022		Class A
ESD	EN 61000-4-2	A	±8 kV Air
			±6 kV Contact
RS	EN 61000-4-3	A	10V/m
EFT, See Note 6	EN 61000-4-4	A	±2 kV
Surge, See Note 6	EN 61000-4-5	A	±1 kV
CS	EN 61000-4-6	A	10 Vrms
PFMF	EN 61000-4-8	A	3A/M

Environmental

Parameter	Conditions	Min.	Typ.	Max.	Units
Operating Temperature Range	Ambient	-40		+80	°C
	Case			+95	
Storage Temperature Range		-50		+125	°C
Cooling	Free Air Convection				
Humidity	RH, Non-condensing			95	%

Physical

Case Size	See Mechanical Diagram (Page 2)
Case Material	Non-Conductive Black Plastic (UL-94V0)
Weight	0.14 Oz (3.9g)

Reliability Specifications

Parameter	Conditions	Min.	Typ.	Max.	Units
MTBF	MIL HDBK 217F, 25°C, Gnd Benign	3.45			MHours
Safety Standards	UL 60950, EN 60950				

Absolute Maximum Ratings

Parameter	Conditions	Min.	Typ.	Max.	Units
Input Voltage Surge (1 Sec)	5 VDC Input			12.0	VDC
	12 VDC Input			25.0	
	24 VDC Input			50.0	
	48 VDC Input			100.0	
Lead Temperature	1.5 mm From Case For 10 Sec			260	°C

Caution: Exceeding Absolute Maximum Ratings may damage the module. These are not continuous operating ratings.

MicroPower Direct
292 Page Street
Suite D
Stoughton, MA 02072
USA

T: (781) 344-8226
F: (781) 344-8481
E: sales@micropowerdirect.com
W: www.micropowerdirect.com


Model Selection Guide

Model Number	Input				Output			Capacitive Load (µF Max)	Efficiency (%, Typ)	Fuse Rating Slow-Blow (mA)
	Voltage (VDC)		Current (mA)		Voltage (VDC)	Current (mA, Max)	Current (mA, Min)			
	Nominal	Range	Full-Load	No-Load						
MH305S-03RW	5	4.5 - 10.0	501	45	3.3	600.0	0.0	100	79	2,000
MH305S-05RW	5	4.5 - 10.0	741	45	5.0	600.0	0.0	100	81	2,000
MH305S-12RW	5	4.5 - 10.0	706	45	12.0	250.0	0.0	100	85	2,000
MH305S-15RW	5	4.5 - 10.0	706	45	15.0	200.0	0.0	100	85	2,000
MH305D-05RW	5	4.5 - 10.0	732	45	±5.0	±300.0	0.0	100	82	2,000
MH305D-12RW	5	4.5 - 10.0	714	45	±12.0	±125.0	0.0	100	84	2,000
MH305D-15RW	5	4.5 - 10.0	706	45	±15.0	±100.0	0.0	100	85	2,000
MH312S-03RW	12	9.0 - 18.0	206	27	3.3	600.0	0.0	100	80	1,000
MH312S-05RW	12	9.0 - 18.0	301	27	5.0	600.0	0.0	100	83	1,000
MH312S-12RW	12	9.0 - 18.0	287	27	12.0	250.0	0.0	100	87	1,000
MH312S-15RW	12	9.0 - 18.0	287	27	15.0	200.0	0.0	100	87	1,000
MH312D-05RW	12	9.0 - 18.0	298	27	±5.0	±300.0	0.0	100	84	1,000
MH312D-12RW	12	9.0 - 18.0	291	27	±12.0	±125.0	0.0	100	86	1,000
MH312D-15RW	12	9.0 - 18.0	287	27	±15.0	±100.0	0.0	100	87	1,000
MH324S-03RW	24	18.0 - 36.0	103	16	3.3	600.0	0.0	100	80	500
MH324S-05RW	24	18.0 - 36.0	151	16	5.0	600.0	0.0	100	83	500
MH324S-12RW	24	18.0 - 36.0	144	16	12.0	250.0	0.0	100	87	500
MH324S-15RW	24	18.0 - 36.0	144	16	15.0	200.0	0.0	100	87	500
MH324D-05RW	24	18.0 - 36.0	149	16	±5.0	±300.0	0.0	100	84	500
MH324D-12RW	24	18.0 - 36.0	145	16	±12.0	±125.0	0.0	100	86	500
MH324D-15RW	24	18.0 - 36.0	144	16	±15.0	±100.0	0.0	100	87	500
MH348S-03RW	48	36.0 - 75.0	52	10	3.3	600.0	0.0	100	79	200
MH348S-05RW	48	36.0 - 75.0	76	10	5.0	600.0	0.0	100	82	200
MH348S-12RW	48	36.0 - 75.0	73	10	12.0	250.0	0.0	100	86	200
MH348S-15RW	48	36.0 - 75.0	73	10	15.0	200.0	0.0	100	86	200
MH348D-05RW	48	36.0 - 75.0	76	10	±5.0	±300.0	0.0	100	82	200
MH348D-12RW	48	36.0 - 75.0	74	10	±12.0	±125.0	0.0	100	85	200
MH348D-15RW	48	36.0 - 75.0	74	10	±15.0	±100.0	0.0	100	85	200


Notes:
1. The specified maximum capacitive load is for each output.
2. Cross regulation is measured with the main output set at 100% load. The second output is varied from 75% to 100% load.
3. When measuring output ripple, it is recommended that an external 0.47 µF ceramic capacitor is connected from the +VOUT to the -VOUT pins. If the application is noise sensitive; connecting a low ESR 3.3 µF capcitor should be used. This capacitor should be mounted as close to the converter as possible.
4. Transient recovery is measured to within a 1% error band for a load step change of 25%.
5. Output overload protection is provided by a fold back current limiting circuit with auto-recovery. A long-term overload could damage the unit.
6. To meet the specified EN 61000-4-4 and EN 61000-4-5 limits, an external capacitor must be connected across the input pins of the module. A 220 µF/100V capacitor is recommended. This capacitor should be mounted as close to the module as possible.
7. Operation at no load will not damage these units.
8. It is recommended that a fuse be used on the input of a power supply for protection. See the Model Selection table above for the correct rating.

A 2W version of this module is also available
For more information see the **MH200RW** series datasheet.
Or call the factory at 781-344-8226

Mechanical Dimensions




Derating Curve



Pin Connections

Pin	Single
1	-VIN
4	+VIN
5	+VOUT
6	No Pin
7	-VOUT

Pin	Dual
1	-VIN
4	+VIN
5	+VOUT
6	Common
7	-VOUT



Notes:
- All dimensions are typical in inches (mm)
- Tolerance x.xx = ±0.02 (±0.5)
- Pin 1 is marked by a "dot" or indentation on the unit

MicroPower Direct
We Power Your Success - For Less!
292 Page Street Ste D Stoughton, MA 02072 • TEL: (781) 344-8226 • FAX: (781) 344-8481 • E-Mail: sales@micropowerdirect.com