**HARTING**®

**Pushing Performance**

# Han 24HPR EasyCon Cover 1xM50



Image is for illustration purposes only. Please refer to product description.

| Part number | 19 40 024 9918 |
|---|---|
| Specification | Han 24HPR EasyCon Cover 1xM50 |
| HARTING eCatalogue | https://b2b.harting.com/19400249918 |

## Identification

| Category | Hoods/Housings |
|---|---|
| Series of hoods/housings | Han® HPR EasyCon |
| Type of hood/housing | Mounting cover |
| Description of hood/housing | for surface mounted housings<br>for hoods |

## Version

| Locking type | Screw locking |
|---|---|
| Size | 24 HPR |
| Cable entry | 1x M50 |
| Field of application | Hoods/housings for harsh outdoor environments |

## Technical characteristics

| Tightening torque | 6 Nm Mounting cover<br>6 Nm Distance bolt |
|---|---|
| Limiting temperature | -40 ... +125 °C |
| Degree of protection acc. to IEC 60529 | IP65<br>IP68<br>IP69 / IPX9K acc. to ISO 20653 |
| Type rating acc. to UL 50 / UL 50E | 4<br>4X<br>12 |

Page 1 / 2 | Creation date 2020-04-06 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.
HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany
Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

**HARTING**

**Pushing Performance**

## Material properties

| | |
|---|---|
| Material (hood/housing) | Aluminium die-cast |
| | Corrosion resistant |
| Surface (hood/housing) | Powder-coated |
| Colour (hood/housing) | RAL 9005 (jet black) |
| Material (seal) | NBR |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

## Specifications and approvals

| | |
|---|---|
| Approvals | DNV GL |
| UL / CSA | UL 1977 ECBT2.E235076 |
| | CSA-C22.2 No. 182.3 ECBT8.E235076 |

## Commercial data

| | |
|---|---|
| Packaging size | 1 |
| Net weight | 224.1 g |
| Country of origin | Germany |
| European customs tariff number | 85389099 |
| eCl@ss | 27440208 Cap for industrial connectors |

Page 2 / 2 | Creation date 2020-04-06 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.
HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany
Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com