



Transformer Connectors

RKW 110/ 2 red

Terminal Block Lift Terminals, 2 pole, red, Voltage Rating: 750 V, Cross-Section: 16.0 mm²



Order Info

Reference Number (ref. no.)	238082
Applications	Transformers
PU	25
EAN	4028012108640

Type

Type	Terminal Block Lift Terminals
Number of poles	2 pole
Clamping Units per Pole	1
Colour	red
Cross-Section	16.0 mm ²
Connection Type	Löt-Schraub

Technical Data

Voltage Rating	750 V
Current Rating	76 A
Insulating Material	PA 6.6
Contact Material	Brass
Core Cross-Section min.	2.5 mm ²
Core Cross-Section max.	16.0 mm ²
Flammability Rating	V-2
max. Ambient Temperature Operation	85 °C
Type of Conductor Solid	yes
Type of Conductor Flexible	yes
Type of Conductor Stranded	yes
Stripping Length	13.0-14.0 mm
Assembly Contact Screw	Imbus 3 / ⚙ 2.5 Nm
Approbation EN60998	RKW110_EN60998_20070830_VDE_40021971_web.pdf
Approbation UL	RKW110_19941130_19941222_UL_E63492_1-13_Description_web.
Approbation CSA	Trafoklemmen_20160615_CSA_70073973_Certificate_web.pdf

Accessories

BZ 14 RU	293800
BZ 14 U	293300