

PFE500SA-48



<b>Sales Region</b>	Worldwide
<b>Series</b>	PFE-SA
<b>Status</b>	Production
<b>Feature</b>	
<b>Option</b>	
<b>Option Lineup</b>	<a href="#">Please refer to here.</a>
<b>Recommended EMC Filter</b>	
<b>Accessories</b>	<a href="#">Please refer to the catalog</a>



**Electrical Characteristics**

Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	
Efficiency	91% Typ.
Rated Output Voltage[DC]	48V
Output Voltage Range[DC]	38.4 to 57.6V
Maximum Output Current	10.5A
Maximum Output Power	504W

**Cases Shape & Size**

Case shape	On board/Power module
Width(W)	61mm Nom.
Height(H)	12.7mm Nom.
Depth(D)	116.8mm Nom.
Weight	200g Typ.

**Other**

Operating Temp. Range	-40 to 100°C
Cooling	Conduction cooling
Safety Standard(Certified)	UL60950-1 CSA C22.2 No.60950-1 EN60950-1

**Safety Standard(Conformed)**

**Remarks** This page only shows representative characteristics. Please refer to the technical data for detailed specifications and conditions.

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.