KODENSHI AUK


STC401

NPN Silicon Transistor

Features

- Low saturation switching application
- Voltage regulator application
- Low saturation : $V_{CE(SAT)}$=0.4V Max.
- High Voltage : V_{CEO}=60V Min.

PIN Connection



TO-92

Ordering Information

Type NO.	Marking	Package Code
STC401	STC401	TO-92

Absolute maximum ratings

Characteristic	Symbol	Ratings	Unit
Collector-Base voltage	V_{CBO}	80	V
Collector-Emitter voltage	V_{CEO}	60	V
Emitter-base voltage	V_{EBO}	5	V
Collector current	I_C	1	A
Collector dissipation	P_C	500	mW
Junction temperature	T_j	150	°C
Storage temperature	T_{stg}	-55~150	°C

Electrical Characteristics

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Collector-Base breakdown voltage	BV_{CBO}	I_C=100 ㎂, I_E=0	80	-	-	V
Collector-Emitter breakdown voltage	BV_{CEO}	I_C=1mA, I_B=0	60	-	-	V
Emitter-Base breakdown voltage	BV_{EBO}	I_E=10mA, I_C=0	5	-	-	V
Collector cut-off current	I_{CBO}	V_{CB}=60V, I_E=0	-	-	0.1	μA
Emitter cut-off current	I_{EBO}	V_{EB}=5V, I_C=0	-	-	0.1	μA
DC current gain	h_{FE} *	V_{CE}=2V, I_C=100mA	200	-	400	-
		V_{CE}=2V, I_C=1A	80	-	-	
Base-Emitter on voltage	$V_{BE(ON)}$	V_{CE}=2V, I_C=500mA	-	-	1.2	V
Collector-Emitter saturation voltage	$V_{CE(sat)}$	I_C=500mA, I_B=50mA	-	-	0.4	V
Collector output capacitance	C_{ob}	V_{CB}=10V, I_E=0, f=1MHz	-	10	-	pF
Transition frequency	f_T	V_{CB}=10V, I_C=50mA	-	160	-	MHz

* h_{FE} rank : 200~400 Only

Electrical Characteristic Curves

Fig. 1 P_C - Ta




Fig. 2 V_{CE} - I_C




Fig. 3 h_{FE}-I_C




Fig. 4 Cob - V_{CB}




Fig. 5 I_C - V_{CE}






Fig. 6 I_C - V_{CE}




Electrical Characteristic Curves

Fig. 7 f_T - I_C



Outline Dimension



SYMBOL	MILLMETERS(mm)		
	MINIMUM	NOMINAL	MAXIMUM
A	3.40	3.50	3.66
A1	2.46	2.51	2.59
b	0.39	0.44	0.53
b1	0.39	–	0.63
c	0.35	0.42	0.47
D	4.48	4.60	4.70
E	4.48	4.60	4.70
e	1.17	1.27	1.37
L	13.70	14.00	14.77
L1	1.55	1.70	2.15

The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.