



CSD75208W1015 Dual 20-V Common Source P-Channel NexFET™ Power MOSFET

1 Features

- Dual P-Channel MOSFETs
- Common Source Configuration
- Small Footprint 1 mm × 1.5 mm
- Gate-Source Voltage Clamp
- Gate ESD Protection –3 kV
- Pb Free
- RoHS Compliant
- Halogen Free


2 Applications

- Battery Management
- Load Switch
- Battery Protection

3 Description

This device is designed to deliver the lowest on-resistance and gate charge in the smallest outline possible with excellent thermal characteristics in an ultra-low profile. Low on-resistance coupled with the small footprint and low profile make the device ideal for battery operated space constrained applications.

Top View



P0059-01

Product Summary

$T_A = 25^\circ\text{C}$		TYPICAL VALUE		UNIT
V_{DS}	Drain-to-Source Voltage	–20		V
Q_g	Gate Charge Total (–4.5 V)	1.9		nC
Q_{gd}	Gate Charge Gate-to-Drain	0.23		nC
$R_{DS(on)}$	Drain-to-Source On-Resistance	$V_{GS} = -1.8\text{ V}$	100	m Ω
		$V_{GS} = -2.5\text{ V}$	70	m Ω
		$V_{GS} = -4.5\text{ V}$	56	m Ω
$R_{D1D2(on)}$	Drain-to-Drain On-Resistance	$V_{GS} = -1.8\text{ V}$	190	m Ω
		$V_{GS} = -2.5\text{ V}$	120	m Ω
		$V_{GS} = -4.5\text{ V}$	90	m Ω
$V_{GS(th)}$	Threshold Voltage	–0.8		V

Ordering Information⁽¹⁾

Device	Qty	Media	Package	Ship
CSD75208W1015	3000	7-Inch Reel	1.0 mm × 1.5 mm	Tape and Reel
CSD75208W1015T	250	7-Inch Reel	Wafer Level Package	

(1) For all available packages, see the orderable addendum at the end of the data sheet.


Absolute Maximum Ratings

$T_A = 25^\circ\text{C}$		VALUE	UNIT
V_{DS}	Drain-to-Source Voltage	–20	V
V_{GS}	Gate-to-Source Voltage	–6	V
I_{D1D2}	Continuous Drain-to-Drain Current, $T_C = 25^\circ\text{C}$	–1.6	A
	Pulsed Drain-to-Drain Current, $T_C = 25^\circ\text{C}$ ⁽¹⁾	–22	A
I_S	Continuous Source Pin Current	–3	A
	Pulsed Source Pin Current ^{(1) (2)}	–39	A
I_G	Continuous Gate Clamp Current	–0.5	A
	Pulsed Gate Clamp Current ⁽¹⁾	–7	A
P_D	Power Dissipation	0.75	W
T_J, T_{stg}	Operating Junction and Storage Temperature Range	–55 to 150	$^\circ\text{C}$

(1) Max $R_{\theta JA} = 165^\circ\text{C/W}$, pulse duration $\leq 100\text{ }\mu\text{s}$, duty cycle $\leq 1\%$

(2) Both devices in parallel

$R_{D1D2(on)}$ vs V_{GS}



$R_{DS(on)}$ vs V_{GS}




Table of Contents

1 Features	1	6 Device and Documentation Support.....	7
2 Applications	1	6.1 Trademarks	7
3 Description	1	6.2 Electrostatic Discharge Caution.....	7
4 Revision History.....	2	6.3 Glossary	7
5 Specifications.....	3	7 Mechanical, Packaging, and Orderable Information	8
5.1 Electrical Characteristics.....	3	7.1 CSD75208W1015 Package Dimensions	8
5.2 Thermal Information	3	7.2 Recommended PCB Land Pattern.....	9
5.3 Typical MOSFET Characteristics.....	4	7.3 Tape and Reel Information	9

4 Revision History

DATE	REVISION	NOTES
July 2014	*	Initial release.

5 Specifications

5.1 Electrical Characteristics

 $T_A = 25^\circ\text{C}$ unless otherwise stated

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
STATIC CHARACTERISTICS						
BV _{DSS}	Drain-to-Source Voltage	V _{GS} = 0 V, I _{DS} = −250 μA	−20			V
BV _{GSS}	Gate-to-Source Voltage	V _{DS} = 0 V, I _G = −250 μA	−6.1		−7.2	V
I _{DSS}	Drain-to-Source Leakage Current	V _{GS} = 0 V, V _{DS} = −16 V			−1	μA
I _{GSS}	Gate-to-Source Leakage Current	V _{DS} = 0 V, V _{GS} = −6 V			−100	nA
V _{GS(th)}	Gate-to-Source Threshold Voltage	V _{DS} = V _{GS} , I _{DS} = −250 μA	−0.5	−0.8	−1.1	V
R _{DS(on)}	Drain-to-Source On-Resistance	V _{GS} = −1.8 V, I _D = −1 A		100	150	mΩ
		V _{GS} = −2.5 V, I _D = −1 A		70	88	mΩ
		V _{GS} = −4.5 V, I _D = −1 A		56	68	mΩ
R _{D1D2(on)}	Drain-to-Drain On-Resistance	V _{GS} = −1.8 V, I _{D1D2} = −1 A		190	285	mΩ
		V _{GS} = −2.5 V, I _{D1D2} = −1 A		120	150	mΩ
		V _{GS} = −4.5 V, I _{D1D2} = −1 A		90	108	mΩ
g _{fs}	Transconductance	V _{DS} = −2 V, I _D = −1 A		7.5		S
DYNAMIC CHARACTERISTICS						
C _{ISS}	Input Capacitance	V _{GS} = 0 V, V _{DS} = −10 V, f = 1 MHz		315	410	pF
C _{OSS}	Output Capacitance			132	172	pF
C _{RSS}	Reverse Transfer Capacitance			7.7	10	pF
Q _g	Gate Charge Total (−4.5 V)	V _{DS} = −10 V, I _{DS} = −1 A		1.9	2.5	nC
Q _{gd}	Gate Charge, Gate-to-Drain			0.23		nC
Q _{gs}	Gate Charge, Gate-to-Source			0.48		nC
Q _{g(th)}	Gate Charge at V _{th}			0.31		nC
Q _{OSS}	Output Charge	V _{DS} = −10 V, V _{GS} = 0 V		2.1		nC
t _{d(on)}	Turn On Delay Time	V _{DS} = −10 V, V _{GS} = −4.5 V, I _{DS} = −1 A, R _G = 0 Ω		9		ns
t _r	Rise Time			5		ns
t _{d(off)}	Turn Off Delay Time			29		ns
t _f	Fall Time			11		ns
DIODE CHARACTERISTICS						
V _{SD}	Diode Forward Voltage	I _{DS} = −1 A, V _{GS} = 0 V	−0.75		−1	V
Q _{rr}	Reverse Recovery Charge	V _{DD} = −10 V, I _F = −1 A, di/dt = 200 A/μs		4.3		nC
t _{rr}	Reverse Recovery Time			9		ns

5.2 Thermal Information


 $T_A = 25^\circ\text{C}$ unless otherwise stated

THERMAL METRIC		MIN	TYP	MAX	UNIT
$R_{\theta JA}$	Junction-to-Ambient Thermal Resistance ⁽¹⁾ ⁽²⁾		165		$^\circ\text{C}/\text{W}$
	Junction-to-Ambient Thermal Resistance ⁽²⁾ ⁽³⁾		95		


⁽¹⁾ Device mounted on FR4 material with minimum Cu mounting area

⁽²⁾ Measured with both devices biased in a parallel condition.

⁽³⁾ Device mounted on FR4 material with 1-inch² (6.45-cm²), 2-oz. (0.071-mm thick) Cu.



Typ $R_{\theta JA} = 95^{\circ}\text{C/W}$
when mounted on
1 inch² (6.45 cm²) of
2-oz. (0.071-mm thick)
Cu.



Typ $R_{\theta JA} = 165^{\circ}\text{C/W}$
when mounted on
minimum pad area of
2-oz. (0.071-mm thick)
Cu.

5.3 Typical MOSFET Characteristics

($T_A = 25^{\circ}\text{C}$ unless otherwise stated)




Figure 1. Transient Thermal Impedance




Figure 2. Saturation Characteristics




Figure 3. Transfer Characteristics




Figure 4. Gate Charge

Typical MOSFET Characteristics (continued)

($T_A = 25^\circ\text{C}$ unless otherwise stated)




Figure 5. Capacitance




Figure 6. Threshold Voltage vs Temperature




Figure 7. On-State Drain-to-Drain Resistance vs Gate-to-Source Voltage




Figure 8. On-State Drain-to-Source Resistance vs Gate-to-Source Voltage




Figure 9. Normalized On-State Resistance vs Temperature




Figure 10. Typical Diode Forward Voltage

Typical MOSFET Characteristics (continued)

($T_A = 25^\circ\text{C}$ unless otherwise stated)




Figure 11. Maximum Safe Operating Area




Figure 12. Maximum Drain Current vs Temperature

6 Device and Documentation Support

6.1 Trademarks

NexFET is a trademark of Texas Instruments.
All other trademarks are the property of their respective owners.

6.2 Electrostatic Discharge Caution



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.

6.3 Glossary


[SLYZ022](#) — *TI Glossary*.

This glossary lists and explains terms, acronyms, and definitions.

7 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

7.1 CSD75208W1015 Package Dimensions




NOTE: All dimensions are in mm (unless otherwise specified).

Pinout

POSITION	DESIGNATION
B1, B2	Source
C1	Gate1
C2	Drain1
A2	Gate2
A1	Drain2


7.2 Recommended PCB Land Pattern



M0158-01

NOTE: All dimensions are in mm (unless otherwise specified).

7.3 Tape and Reel Information



M0159-01

NOTE: All dimensions are in mm (unless otherwise specified).

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
CSD75208W1015	ACTIVE	DSBGA	YZC	6	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM	-40 to 85	75208	Samples
CSD75208W1015T	ACTIVE	DSBGA	YZC	6	250	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM	-40 to 85	75208	Samples

(1) The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBsolete: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Applications Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive and Transportation	www.ti.com/automotive
Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Video and Imaging	www.ti.com/video

TI E2E Community

e2e.ti.com