
Inductors

Subminiature, Shielded



FEATURES

- Classification is Grade 1, Class B
- Subminiature shielded
- Inductance range is 0.10 µH to 100 000 µH
- Printed board mounting facilitated by 0.200" [5.08 mm] grid spacing
- Radial lead fixed inductor
- High Q values
- Unitized epoxy-molded construction
- Shielded construction to allow maximum density packaging

RoHS COMPLIANT

ELECTRICAL SPECIFICATIONS

Inductance Tolerance: ± 10 %

Dielectric Strength: 840 VRMS at sea level

Working Voltage: 300 VDC

Q and SRF Values: Minimum not less than 80 % of specified value

Maximum Current: Based on temperature rise not to exceed 35 °C at + 90 °C ambient

MECHANICAL SPECIFICATIONS

Operating Temperature: - 55 °C to + 125 °C

Terminal Pull: 3 pounds

DENSITY SPECIFICATIONS

Weight: 1.5 grams maximum

Shielding: 3 % coupling maximum when two units are tested side by side


ENVIRONMENTAL SPECIFICATIONS


Moisture: Per MIL-STD-202, Method 106

Vibration: Low frequency, 10 Hz to 55 Hz at 0.06" [1.52 mm] maximum total excursion at rate of 1 linear sweep per minute for 2 hours repeated for each of three mutually perpendicular planes

Shock: 100 g, 6 ms, body mounted

DIMENSIONS in inches [millimeters]





STANDARD ELECTRICAL SPECIFICATIONS

MODEL	IND. (µH)	TOL.	Q NOM.	TEST FREQ. (MHz)	SELF-RESONANT FREQ. NOM. (MHz)	DCR MAX. (Ohms)	RATED DC CURRENT (mA)	INCREMENTAL* CURRENT (mA)
PC	0.10	± 10 %	70	25	> 250	0.030	2500	2500
PC	0.12	± 10 %	70	25	> 250	0.030	2500	2500
PC	0.15	± 10 %	70	25	> 250	0.030	2500	2500
PC	0.18	± 10 %	70	25	> 250	0.035	2400	2400
PC	0.22	± 10 %	70	25	> 250	0.038	2300	2300
PC	0.27	± 10 %	80	25	> 250	0.040	2200	2200
PC	0.33	± 10 %	80	25	> 250	0.040	2200	2200
PC	0.39	± 10 %	80	25	250	0.045	2100	2100
PC	0.47	± 10 %	80	25	230	0.045	2100	2100
PC	0.56	± 10 %	80	25	220	0.050	2000	2000

*** Incremental Current:** The DC current required to cause a 5 % reduction in the nominal inductance value.

STANDARD ELECTRICAL SPECIFICATIONS

MODEL	IND. (µH)	TOL.	Q NOM.	TEST FREQ. (MHz)	SELF-RESONANT FREQ. NOM. (MHz)	DCR MAX. (Ohms)	RATED DC CURRENT (mA)	INCREMENTAL* CURRENT (mA)
PC	0.68	± 10 %	80	25	190	0.055	1900	1900
PC	0.82	± 10 %	85	25	180	0.060	1800	1800
PC	1.0	± 10 %	85	25	160	0.070	1700	1700
PC	1.2	± 10 %	90	7.9	170	0.085	1670	1670
PC	1.5	± 10 %	100	7.9	155	0.100	1540	1540
PC	1.8	± 10 %	115	7.9	135	0.110	1470	1470
PC	2.2	± 10 %	110	7.9	120	0.120	1410	1410
PC	2.7	± 10 %	110	7.9	104	0.125	1380	1380
PC	3.3	± 10 %	90	7.9	93	0.165	1200	1200
PC	3.9	± 10 %	90	7.9	87	0.180	1135	1135
PC	4.7	± 10 %	95	7.9	79	0.245	985	985
PC	5.6	± 10 %	95	7.9	72	0.265	950	950
PC	6.8	± 10 %	85	7.9	63	0.330	853	853
PC	8.2	± 10 %	95	7.9	60	0.460	720	720
PC	10	± 10 %	90	7.9	54	0.640	620	620
PC	12	± 10 %	120	2.5	37	0.800	545	545
PC	15	± 10 %	120	2.5	28.8	0.865	520	520
PC	18	± 10 %	115	2.5	23.8	0.940	504	504
PC	22	± 10 %	125	2.5	21.3	1.03	460	460
PC	27	± 10 %	115	2.5	20.6	1.18	418	418
PC	33	± 10 %	120	2.5	18.6	1.30	398	398
PC	39	± 10 %	120	2.5	17.7	1.41	385	385
PC	47	± 10 %	110	2.5	14.9	1.61	350	350
PC	56	± 10 %	115	2.5	13.9	2.08	330	333
PC	68	± 10 %	105	2.5	12.9	2.20	320	330
PC	82	± 10 %	105	2.5	11.7	2.42	300	320
PC	100	± 10 %	95	2.5	10.5	2.15	333	300
PC	120	± 10 %	95	0.79	5.6	2.38	316	190
PC	150	± 10 %	90	0.79	5.2	2.52	306	175
PC	180	± 10 %	95	0.79	4.9	2.88	288	150
PC	220	± 10 %	95	0.79	4.6	3.18	273	125
PC	270	± 10 %	100	0.79	4.2	3.50	260	120
PC	330	± 10 %	100	0.79	3.55	4.80	222	110
PC	390	± 10 %	100	0.79	3.45	5.44	209	105
PC	470	± 10 %	100	0.79	3.2	5.9	201	100
PC	560	± 10 %	95	0.79	2.9	6.3	194	90
PC	680	± 10 %	100	0.79	2.7	7.2	181	80
PC	820	± 10 %	90	0.79	2.5	8.0	172	70
PC	1000	± 10 %	100	0.79	2.35	12	141	65

*** Incremental Current:** The DC current required to cause a 5 % reduction in the nominal inductance value.

MARKING

- Manufacturer data printed

ORDERING INFORMATION

PC	0.10 µH	10 %	EB	e2
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD

GLOBAL PART NUMBER



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.