



技术说明

- 1.表明光洁，无明显缩坑与熔接痕
- 2.Current rating:14A AC/DC  
额定电流：14A AC/DC
- 3.工作温度：-40℃- +125℃

K 282103 T M - B SN - X  
 ①      ②      ③ ④      ⑤      ⑥      ⑦

- 1.K: XKBTEK-Car Connector
- 2.XKB Series No
- 3.Category:T-Terminal
- 4.Special No:M-Male Terminal
- 5.Material:B-H65
- 6.Plating:SN-Plated Tin
- 7.Type:H-High foot ; L-Middle foot  
M-Low feet

K282103TM-BSN-M	AWG#22-20	2.5	2.3	1.2	5.2	4.7	2.1
K282103TM-BSN-L	AWG#18-15	3.2	3.3	1.2	5.2	4.7	2.1
K282103TM-BSN-H	AWG#15-13	3.6	3.8	1.2	5.2	4.7	2.1
PART NO	Wire Range	U	V	W	X	Y	Z

K282103TM-BSN-X	H65	K282103HF	K282103D
PART NO	Material	Suitable XKB Female	Suitable XKB Plug

DSND		SCALE: N/A	MODEL TYPE: 6.0mm Automobile connector
DWN		VIEW:	PART NO.: K282103TM-BSN-X
CHKD		UNIT: mm/in	DWG NO.: X-K282103TM-BSN-X
APPD		SIZE: A4	

					ANGULAR	±5°
ΔX					L ≤ 4	±0.2
ΔX					4 < L ≤ 16	±0.3
ΔX					16 < L ≤ 63	±0.4
MARK					L > 63	±0.5
REVISIONS					UNSPECIFIED TOLERANCES	
www.helloxkb.com www.helloxkb.cn www.xk-dg.cn						



XKB INDUSTRIAL PRECISION CO., LIMITED

WEIGHT	SHEET	REVISION
	1/1	A0