




LOW VOLTAGE RECTIFIER Transformers with horizontal channel frames.

- Primary voltage, 115 Volts, 60 Hz.
- Primary and secondary leads 8-10" long.
- 2-hole horizontal mounting.
- 6 sizes are available, covering the range: 1 to 10 VA.
- CSA listed (LR 47366).



### MECHANICAL



Dimensions, Inches

P/N	DIMENSIONS			PIN SPACING A
	L	W	H	
4760	2.06	1.25	1.19	1.75
4761	2.06	1.38	1.19	1.75
4762	2.38	1.38	1.38	2.00
4763	2.38	1.50	1.38	2.00
4764	2.81	1.88	1.69	2.38
4765	2.81	2.00	1.69	2.38

### ELECTRICAL SPECIFICATION

Part No.	Secondary Voltages (A-A)		
	F.L. Volts	N.L. Volts	Current Amps
4760-01	5.0	6.11	0.250
4760-02	6.3	7.45	0.150
4761-01	14.0	17.50	0.150
4761-02	20.0	24.50	0.100
4762-01	5.0	5.83	0.500
4762-02	6.3	7.10	0.300
4762-03	6.3	7.80	0.600
4762-04	10.0	12.40	0.300
4762-05	12.6	15.70	0.300
4762-06	20.0	23.50	0.150
4762-07	25.0	28.80	0.100
4762-08	25.0	30.80	0.150
4762-09	50.0	62.00	0.075
4763-01	5.0	6.17	1.000
4763-02	7.0	8.30	0.700
4763-03	8.0	9.52	0.500
4763-04	9.0	10.90	0.500
4763-05	16.0	18.60	0.250
4763-06	30.0	37.40	0.150

Part No.	Secondary Voltages (A-A)		
	F.L. Volts	N.L. Volts	Current Amps
4764-01	6.3	7.10	1.000
4764-02	10.0	11.00	0.500
4764-03	12.6	14.50	0.500
4764-04	14.0	16.10	0.500
4764-05	20.0	22.80	0.300
4764-06	25.0	29.00	0.300
4764-07	30.0	36.10	0.250
4764-08	36.0	40.70	0.150
4764-09	44.0	51.60	0.150
4765-01	8.5	9.60	1.000
4765-02	16.0	18.00	0.500
4765-03	28.0	31.70	0.250