# Product data sheet
## Characteristics

# 9422BTCF30
## Operating mechanism, flange mounted, fixed depth assembly, 30A, 250 V, fuseholder, switch mechanism, 6 inch handle

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 543.00 USD



## Main

| | |
|---|---|
| Range | 9422T |
| Product | Disconnect Switch |
| Disconnect Type | Fusible disconnect switch |

## Complementary

| | |
|---|---|
| Mounting Type | Bracket fixed depth |
| Current Rating | 30 A |
| Horsepower Rating | 7.5 hp 200 V AC<br>7.5 hp 230 V AC<br>15 hp 460 V AC<br>20 hp 575 V AC<br>5 hp 250 V DC |
| Fuse Rating | 30 A 250 V |
| Handle Type | 6 in handle included |
| Fuse Type | K<br>R<br>J<br>H |

## Environment

| | |
|---|---|
| Certifications | UL Recognized<br>CSA |

## Ordering and shipping details

| | |
|---|---|
| Category | 21732 - 9422 |

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| Discount Schedule | CP1 |
| GTIN | 00785901885184 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 13 lb(US) (5.90 kg) |
| Returnability | No |
| Country of origin | MX |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |