SF1001ET(D) THRU SF1006ET(D)

Reverse Voltage -100 to 600 Volts Forward Current - 10.0 Ampere


SUPER FAST GLASS PASSIVATED RECTIFIERS

FEATURES


- High current capability
- Low forward voltage drop
- Low power loss, high efficiency
- High surge capability
- High temperature soldering guaranteed
- Mounting position: any


TO-251(I-PAK)





TO-252(D-PAK)





MECHANICAL DATA

Case: TO-251/252 molded plastic body
Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026
Polarity: Color band denotes cathode end
Mounting Position: Any
Weight:0.0141 ounce(approx), 0.4 grams (approx)

PACKAGE SPECIFICATIONS

Package	Reel Size	Reel DIA. (mm)	Q'TY/Reel (pcs)	Box Size (mm)	QTY/Box (pcs)	Carton Size (mm)	Q'TY/Carton (pcs)
TO-251	13'	330	2500	340×336×29	2500	353×346×365	25000
TO-252	13'	330	2500	340×336×29	2500	353×346×365	25000

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25℃ ambient temperature unless otherwise specified.
Single phase half-wave 60Hz,resistive or inductive load,for capacitive load current derate by 20%.

MCHARACTERISTICS	TO-251 / TO-252	SF 1001ET / SF 1001ED	SF 1002ET / SF 1002ED	SF 1003ET / SF 1003ED	SF 1004ET / SF 1004ED	SF 1005ET / SF 1005ED	SF 1006ET / SF 1006ED	UNITS
Maximum repetitive peak reverse voltage	V_{RRM}	100	200	300	400	500	600	V
Maximum RMS voltage	V_{RMS}	70	140	210	280	350	420	V
Maximum DC blocking voltage	V_{DC}	100	200	300	400	500	600	V
Maximum average forward rectified current	$I_{(AV)}$	10.0						A
Peak forward surge current 8.3ms single half sine-wave superimposed onrated load (JEDEC Method)	I_{FSM}	170						A
Maximum instantaneous forward voltage at 10.0A DC	V_F	0.95		1.30		1.70		V
Maximum DC reverse current T_A=25℃ at rated DC blocking voltage T_A=125℃	I_R	1.0 300						uA
Typical junction capacitance (NOTE 1)	C_J	45						pF
Typical thermal resistance (NOTE 2)	$R_{\theta JA}$	15						℃/W
Maximum Reverse Recovery Time(Note3)	Trr	35						ns
Operating junction and storage temperature range	T_J,T_{STG}	-55 to +150						℃

Note:1.Measured at 1.0MHz and applied reverse voltage of 4.0V D.C.
2.Mounted on 10cm x 10cm x 1mm copper pad area
3.Reverse Recovery Test Conditions:IF=0.5A,IR=1A,Irr=0.25A
4.The typical data above is for reference only.

DN:T19221A0

Download from alldatasheet.com

Rating and Characteristic Curves

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS





FIG.5 - TYPICAL JUNCTION CAPACITANCE




The curve above is for reference only.

Download from alldatasheet.com

Outlitne Drawing

TO-252(D-PAK) Package Outline Dimensions




TO-252(D-PAK) mechanical data

UNIT		A	B	b	C	D	E	F	G	H	L	L1	L2	L3	S	M	N	J	K	T
mm	max	6.7	5.5	0.8	2.5	6.3	0.6	1.8	2.29 TYPICAL	0.55	3.1	1.2	1.0	1.75	0.1	1.8 TYPICAL	1.3 TYPICAL	3.16 ref.	1.80 ref.	4.83 ref.
	min	6.3	5.1	0.3	2.1	5.9	0.4	1.3		0.45	2.7	0.8	0.6	1.40	0.0					
mil	max	264	217	31	98	248	24	71	90 TYPICAL	22	122	47	39	69	4	71 TYPICAL	51 TYPICAL	124 ref.	71 ref.	190 ref.
	min	248	201	12	83	232	16	51		18	106	31	24	55	0					

Download from alldatasheet.com

Outlitne Drawing

TO-251(I-PAK) Package Outline Dimensions



TO-251(I-PAK) mechanical data

UNIT		A	B	b	b1	C	D	E	F	G	H	L	L1	M	N
mm	max	6.70	5.50	0.80	0.90	2.50	6.30	0.60	1.80	2.29 TYPICAL	0.55	4.30	1.20	1.8 TYPICAL	1.3 TYPICAL
	min	6.30	5.10	0.30	0.76	2.10	5.90	0.40	1.30		0.45	3.90	0.80		
mil	max	264	217	31	35	98	248	24	71	90 TYPICAL	22	169	47	71 TYPICAL	51 TYPICAL
	min	248	201	12	30	83	232	16	51		18	154	31		

Important Notice and Disclaimer

Microdiode Electronics (Jiangsu) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design,purchase or use.

Microdiode Electronics (Jiangsu) makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does Microdiode Electronics (Jiangsu) assume any liability for application assistance or customer product design. Microdiode Electronics (Jiangsu) does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Microdiode Electronics (Jiangsu).

Microdiode Electronics (Jiangsu) products are not authorized for use as critical components in life support devices or systems without express written approval of Microdiode Electronics (Jiangsu).

Download from alldatasheet.com