


SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER
SMB


Dimensions in inches and (millimeters)

FEATURES

- ◆ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆ For surface mounted applications
- ◆ Low reverse leakage
- ◆ Built-in strain relief, ideal for automated placement
- ◆ High forward surge current capability
- ◆ High temperature soldering guaranteed: 250°C/10 seconds at terminals

MECHANICAL DATA






Case: JEDEC SMB molded plastic body
Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
Polarity: Color band denotes cathode end
Mounting Position: Any
Weight : 0.003 ounce, 0.093 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
 Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Catalog Number	SYMBOLS	SS54	UNITS
Maximum repetitive peak reverse voltage	V_{RRM}	40	VOLTS
Maximum RMS voltage	V_{RMS}	28	VOLTS
Maximum DC blocking voltage	V_{DC}	40	VOLTS
Maximum average forward rectified current at T_L (see fig.1)	$I_{(AV)}$	5.0	Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	150.0	Amps
Maximum instantaneous forward voltage at 5.0A	V_F	0.55	Volts
Maximum DC reverse current $T_A=25^\circ\text{C}$ at rated DC blocking voltage $T_A=100^\circ\text{C}$	I_R	0.5 20	mA
Typical junction capacitance (NOTE 1)	C_J	200	pF
Typical thermal resistance (NOTE 2)	$R_{\theta JA}$	50.0	°C/W
Operating junction temperature range	T_J	-50 to +125	°C
Storage temperature range	T_{STG}	-50 to +150	°C

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.
 2. P.C.B. mounted with 0.2x0.2" (5.0x5.0mm) copper pad areas

**AVERAGE FORWARD RECTIFIED CURRENT,
AMPERES**
FIG. 1- FORWARD CURRENT DERATING CURVE

**PEAK FORWARD SURGE CURRENT,
AMPERES**
FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT

FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS

FIG. 4-TYPICAL REVERSE CHARACTERISTICS

FIG. 5-TYPICAL JUNCTION CAPACITANCE

**TRANSIENT THERMAL IMPEDANCE,
°C/W**
FIG. 6-TYPICAL TRANSIENT THERMAL IMPEDANCE
