# Générateur d'air chaud de 250-400 W



## Caractéristiques

- Idéal lorsqu'une puissance calorifique plus importante ou une circulation forcée de l'air intérieur est nécessaire.
- Conçu pour prévenir la condensation et maintenir une température minimale à l'intérieur des enceintes.
- Des thermostats sont aussi disponibles.

| Part No. | Watts | Surface Temperature | Starting Current | Dimensions Length x Width x Depth | Ship Wt. lbs |
|---|---|---|---|---|---|
| **SHGL04600** | 250 | 167°F | 2.2 A | 7.00 x 3.15 x 3.15 | 2 |
| **SHGL04601** | 400 | 167°F | 3.5 A | 9.76 x 3.15 x 3.15 | 3 |

| | |
|---|---|
| Operating Voltage: | AC 110-120 V, 50/60 Hz |
| Circulation Power: | 20 CFM Free Blowing |
| Axial Fan: | Ball Bearing |
| Durability: | 30,000 hrs. at 68°F ambient temperature |
| Heating Element: | Resistance heating element with temperature limiter |
| Heating Body: | Extruded aluminum, black anodized |
| Connection: | 3 pole terminal for 12 AWG |
| Mounting: | Easily installed by clip mounting on 35 mm DIN rails (included) |
| Protection Class: | 1 (tested for grounding at 1250 V) |
| Protection: | IP20 |
| Approval: | UL Recognized Component, cUL Recognized Component, CE |

*Les données sont sujettes à changement sans préavis.*

© 2014. Hammond Manufacturing Ltd. Tous droits réservés.