

P-tec Corp.
2405 Commerce Circle
Alamosa CO 81101
www.p-tec.net

Tel:(866) 695 4162
Tel:(719) 589 3122
Fax:(719) 589 3592
sales@p-tec.net



PL00133 Series SMD LED 0603 Package

Features

- *Flat Lens Thin Package 1.6 x 0.8 x 0.4mm
- *Low Current Requirements
- *High Light Output
- *Compatible with IR Solder-Process
- *Industry Standard Footprint
- *4000 pcs per Reel
- *RoHS Compliant



Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation	84mA
Reverse Voltage ($<10\mu\text{A}$)	5.0V
Max Forward Current	30mA
Peak Forward Current(1/10 Duty Cycle, 0.1ms Pulse Width)	100mA
Operating Temperature Range	-40°C to $+85^\circ\text{C}$
Storage Temperature Range	-40°C to $+85^\circ\text{C}$
Reflow Soldering Temperature	260°C for 10 seconds



Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Dominant Wave Length	Peak Wave Length	Viewing Angle 2 θ 1/2	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
PL00133-WCB11	Blue	InGaN	465	464	130°	3.3	3.5	36.0	57.0

Package Dimensions are in **Millimeters**. Tolerance is $\pm 0.15\text{mm}$ unless otherwise specified.



Cathode Mark



Recommended Soldering Pad Layout

