


CCT261631-30-06-02



<b>Applications</b>	Industrial and Infrastructure
<b>AC / DC</b>	AC
<b>Status</b>	Production



Size	
Length(L)	28.60mm Max.
Width(W)	18.50mm Max.
Height(H)	32.00mm Max.
Internal Clamp Diameter	6.00mm Nom.
Detail Size Information	<a href="#">Please refer to the catalog</a>

Electrical Characteristics	
Applicable Current [50/60Hz]	0.1 to 30Arms
Nominal Current Transformation Ratio	3000:1
Output Current Accuracy	10mA ±0.1mA
Phase Difference	3° ±1.5°
Secondary Winding Resistance	492Ω
Open-circuit Protection	7.5V clamp element
Withstanding Voltage [1min.]	2.2kVAC
Insulation Resistance [DC500V]	100MΩ Min.

Other	
Output Connector (Receptacle Housing)	PALR-02VF (JST)
Adaptable Connector (Plug Housing)	PAP-02V-S (JST)
Output Lead Wire	AWG22 160mm
Flame Retardant Grade	UL 94 V-0
Operating Temp. Range	-20 to 60°C
Packing	Bulk(Polystyrene form)
Package Quantity	60pcs
Weight	24g

! Images are for reference only and show exemplary products.  
! This PDF document was created based on the data listed on the TDK Corporation website.  
! All specifications are subject to change without notice.

