

VPU II 0 PV 600V DC**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Type II surge voltage arrester for use in photovoltaic applications**

- Pluggable arrester
- Suitable for protecting DC systems
- High energy absorption with short response time
- Tested in accordance with EN 50539-11
- Suitable for use in accordance with IEC 60364-7-712 / EN 50539-12
- Coded voltage level
- Installation in distribution board
- Thermal protection function

General ordering data

Version	Surge voltage arrester, Low voltage, Accessories
Order No.	1351320000
Type	VPU II 0 PV 600V DC
GTIN (EAN)	4050118158755
Qty.	1 pc(s).

VPU II 0 PV 600V DC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	64 mm	Depth (inches)	2.52 inch
Height	52 mm	Height (inches)	2.047 inch
Width	17.8 mm	Width (inches)	0.701 inch
Net weight	90 g		

Temperatures

Storage temperature	-40 °C...80 °C	Operating temperature	-40 °C...
---------------------	----------------	-----------------------	-----------

General data

Colour	orange	Design	Installation housing; 1TE, Insta IP 20
Optical function display	green = OK; red = arrester is defective - replace	Protection degree	IP20
Rail	TS 35	UL 94 flammability rating	V-0

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

Photovoltaic technical data

Conditions and requirements	EN 50539-11	Maximum continuous operating voltage UCPV mode +/-, -/PE, +/-PE	600 V DC
PV system voltage, max. U_{cpv}	600 V	Protection level U_p (+/-, -/PE, +/-PE)	≤ 2.2 kV
Protection level U_p at I_n (per module)	≤ 2.2 kV	Short-circuit current I_{scpv}	200 A
Standards	EN 50539-11		

Rated data IEC / EN

Discharge current I_{max} (8/20 μ s) wire-PE	40 kA	Discharge current I_n (8/20 μ s) wire-PE	20 kA
Leakage current at U_n	30 μ A	Max. continuous voltage, U_c (DC)	600 V
Number of poles	1	PV voltage, acc. to IEC 60364-7-712	< 600 V
Protection level U_p at I_n (L/N-PE)	≤ 2.2 kV	Rated voltage (DC)	600 V
Response time	≤ 25 ns	Standards	EN 50539-11
Voltage type	DC		

Connection data

Type of connection	pluggable
--------------------	-----------

Classifications

ETIM 6.0	EC000941	ETIM 7.0	EC000941
ETIM 8.0	EC000941	ECLASS 9.0	27-13-08-05
ECLASS 9.1	27-13-08-05	ECLASS 10.0	27-13-08-05
ECLASS 11.0	27-13-08-05		

VPU II 0 PV 600V DC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Tender specification sheets

Long specification	Spare arrester consisting of V0 material for surge voltage arrester VPU II 600 VDC series The pluggable high-performance varistors can be exchanged by trained personnel following a failure. Rated voltage: 600 VDC for PV systems Type: Weidmüller VPU II 0 PV 600 VDC Order No.: 1351320000	Short specification	Spare arrester for surge voltage arrester VPU II 600 V DC series The pluggable high-performance varistors can be swapped by trained personnel following a failure. Rated voltage: 600 V DC for PV systems Type: Weidmüller VPU II 0 PV 600 V DC Order no.: 1351320000
--------------------	--	---------------------	---

Approvals

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	EAC VPU SERIES EU_Konformitätserklärung / EU_Declaration_of_Conformity
Engineering Data	EPLAN, WSCAD
User Documentation	Beipackzettel / Instruction sheet
Catalogues	Catalogues in PDF-format

VPU II 0 PV 600V DC

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Drawings

