

ADSL MICRO FILTER
P/N: AD-3163 DATA SHEET



Bothhand USA. e-mail: sales@bothhandusa.com http://www.bothhand.com

Feature





- Compact package, includes connectors for ease of installation.
- Design for G.lite Application.
- 100 mA DC Loop Current Capacity.
- Operating Temperature: -10°C to +60°C
- Storage Temperature: -25°C to +75°C.


Electrical Specifications @ 25°C				
POTS Port Impedance	600Ω	Longitudinal Balance	@200Hz~3KHz	-53dB Min
Insertion Loss	@1004Hz	-1dB Max	POTS Tip and Ring DC Voltage	0~105V
3dB Cutoff Frequency	10KHz Typ	DC Resistance each line		7.5Ω Max
Attenuation	@25KHz	-25dB Min	Return Loss	@ERL -6dB Min
	@30KHz	-30dB Min		@SRL -5dB Min
In Band Ripple	-1dB Max		@SRLH	-3dB Min

Schematic

Mechanical



Connector	Function	Style	Tip	Ring
J1	Line	RJ11	Pin3	Pin4
J2	Phone	RJ11	Pin3	Pin4



Units: mm Tolerances: xx.x0±0.25[0.010]
 0.xx±0.05[0.002]