Certificate Number: Q10561

Certificate Number: E17276

AKBL400 - AKBL410

AVALANCHE BRIDGE RECTIFIERS

PRV : 50 - 1000 Volts
Io : 4.0 Amperes


FEATURES :

* High case dielectric strength
* High surge current capability
* High reliability
* Low reverse current
* Low forward voltage drop
* Ideal for printed circuit board
* Pb / RoHS Free

MECHANICAL DATA :

* Case : Reliable low cost construction utilizing molded plastic technique
* Epoxy : UL94V-O rate flame retardant
* Lead : Axial lead solderable per MIL - STD 202 , Method 208 guaranteed
* Polarity : Polarity symbols marked on case
* Mounting position : Any
* Weight : 5.15 grams

KBL



Dimensions in inches and (millimeter)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.
Single phase, half wave, 60 Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

RATING	SYMBOL	AKBL 400	AKBL 401	AKBL 402	AKBL 404	AKBL 406	AKBL 408	AKBL 410	UNIT
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Minimum Avalanche Breakdown Voltage at 100 µA	$V_{BO(min.)}$	100	150	250	450	700	900	1100	V
Maximum Avalanche Breakdown Voltage at 100 µA	$V_{BO(max.)}$	550	600	700	900	1150	1350	1550	V
Maximum Average Forward Current Tc = 50°C	$I_{F(AV)}$	4.0							A
Peak Forward Surge Current Single half sine wave Superimposed on rated load (JEDEC Method)	I_{FSM}	200							A
Rating for fusing at (t < 8.3 ms.)	I^2t	166							A^2S
Maximum Forward Voltage per Diode at I_F = 4.0 A	V_F	1.1							V
Maximum DC Reverse Current Ta = 25 °C	I_R	10							µA
at Rated DC Blocking Voltage Ta = 100 °C	$I_{R(H)}$	1.0							mA
Typical Thermal Resistance (Note1)	RθJA	10							°C/W
Operating Junction Temperature Range	T_J	- 50 to + 150							°C
Storage Temperature Range	T_{STG}	- 50 to + 150							°C

Note :

1) Thermal resistance from Junction to ambient with units mounted on a 3" x 3" x 0.11" (7.5 x 7.5 x 0.3 cm) Cu. plate.

RATING AND CHARACTERISTIC CURVES (AKBL400 - AKBL410)

FIG.1 - DERATING CURVE FOR OUTPUT RECTIFIED CURRENT




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL FORWARD CHARACTERISTICS PER DIODE




FIG.4 - TYPICAL REVERSE CHARACTERISTICS

