SEFM8N18
SEFMN820
SEFP8N18
SEFP8N20

N-CHANNEL POWER MOS TRANSISTORS

HIGH SPEED SWITCHING APPLICATIONS

These products are diffused multi-cell silicon gate N-Channel enhancement mode Power-Mos field effect transistors.


V_{DSS}	$R_{DS\ (ON)}$	I_D
180V/200V	0.4 Ω	8 A

ABSOLUTE MAXIMUM RATINGS

		SEFM or SEFP 8N18	SEFM or SEFP 8N20
V_{DS}	Drain-source voltage (V_{GS} = 0)	180V	200V
V_{DGR}	Drain-gate voltage (R_{GS} = 20KΩ)	180V	200V
V_{GS}	Gate-source voltage	±20V	
I_D	Drain current (continuous) T_{case} = 25°C	8A	
I_{DM}(•)	Drain current (pulsed)	25A	
I_{GM}	Gate current (pulsed)	1.5A	
P_{tot}	Total power dissipation at T_{case} = 25°C	75W	
	Derating factor	0.6W/°C	
T_{stg}	Storage temperature	-65 to 150°C	
T_j	Max. operating junction temperature	150°C	


(•) Pulse width limited by safe operating area

INTERNAL SCHEMATIC DIAGRAM



MECHANICAL DATA

Dimensions in mm



SEFM8N18
SEFMN820
SEFP8N18
SEFP8N20

THERMAL DATA

$R_{th\ j\text{-}case}$	Thermal resistance junction-case	max.	1.67°C/W
T_L	Maximum lead temperature for soldering purpose		275°C

ELECTRICAL CHARACTERISTICS (T_{case} = 25°C unless otherwise specified)

Parameter		Test conditions	Min.	Typ.	Max.	Unit
OFF						
$V_{(BR)\ DSS}$	Drain-source breakdown voltage	I_D = 5 mA V_{GS} = 0 for SEFM8N18/SEFP8N18 for SEFM8N20/SEFP8N20	 180 200			 V V
I_{DSS}	Zero gate voltage drain current (V_{GS} = 0)	V_{DS} = 0.85 Rated V_{DSS} T_j = 100°C			250 2.5	µA mA
I_{GSS}	Gate-body leakage current (V_{DS} = 0)	V_{GS} = ±20 V			500	nA
ON*						
$V_{GS\ (th)}$	Gate threshold voltage	V_{DS} = V_{GS} I_D = 1 m A T_j = 100°C	2 1.5		4.5 4.0	V V
$R_{DS\ (on)}$	Static drain-source on resistance	V_{GS} = 10V I_D = 4 A		0.27	0.4	Ω
$V_{DS\ (on)}$	Drain-source On voltage	V_{GS} = 10V I_D = 8 A V_{GS} = 10V I_D = 4 A T_j = 100°C			4 3.2	V V
g_{fs}	Forward transconductance	V_{DS} = 15V I_D = 4 A	3			mho
DYNAMIC						
C_{iss} C_{oss} C_{rss}	Input capacitance Output capacitance Reverse transfer capacitance	V_{DS} = 25 V f = 1 MHz V_{GS} = 0		980 200 80	1200 260 100	pF pF pF

SEFM8N18
SEFMN820
SEFP8N18
SEFP8N20

ELECTRICAL CHARACTERISTICS (continued)


Parameter		Test conditions	Min.	Typ.	Max.	Unit.
SWITCHING						
$t_{d\ (on)}$	Turn-on delay time	V_{CC} = 25 V		40		ns
t_r	Rise time	I_D = 0.5 Rated I_D		150		ns
$t_{d\ (off)}$	Turn-off delay time	R_{GS} = 50 Ω R_i = 50 Ω		100		ns
t_f	Fall time	(see test circuit)		100		ns
SOURCE DRAIN DIODE						
V_{SD}	Forward on voltage	I_{SD} = Rated I_D V_{GS} = 0		2.0		V
t_{on}	Forward Turn-on time			250		ns
t_{rr}	Reverse recovery time			325		ns

* Pulsed: pulse duration ≤ 300μs, duty cycle ≤ 2%


For typical curves, and clamping inductive load, gate charge, body drain diode trr measurement test circuits see SGSP363 Datasheet.

SWITCHING TIMES RESISTIVE LOAD

Test circuit



Waveforms



Pulse width ≤ 100 μs
Duty cycle ≤ 2%
V_i = 10V