

## ILPA75JU SERIES



## 75W Water-Proof Constant Current LED Driver

- Wide Input Voltage 90 to 305VAC, 47 to 63Hz
- Constant Output Current Available From 350mA To 5000mA
- Over Voltage, Short Circuit, Lighting, and Over Temperature Protection
- High Efficiency (up to 92%)
- Active Power Factor Correction (PFC) (99% typical)
- IP67 Waterproof Rating, Metal Housing
- Comply with UL8750 & EN61347 Safety Regulation

2 Year Warranty

Approvals:    IP67 

### Single Output

Part Number	Output Current Range (Min. / Typ. / Max.)	Output Voltage (Min. / Max.)	Efficiency (220VAC, Full Load)	Over Voltage Protection (Typ. / Max.)	Max. Output Power
ILPA75JU-S500ST	4750 / 5000 / 5250mA	7 / 15 VDC	88%	18 / 25 VDC	75W
ILPA75JU-S210ST	3565 / 3750 / 3935mA	10 / 20 VDC	88%	26 / 30 VDC	75W
ILPA75JU-S280ST	2660 / 2800 / 2940mA	13 / 27 VDC	89%	35 / 38 VDC	75W
ILPA75JU-S3750ST	1995 / 2100 / 2205mA	18 / 36 VDC	89%	42 / 45 VDC	75W
ILPA75JU-S140ST	1330 / 1400 / 1470mA	27 / 54 VDC	90%	65 / 70 VDC	75W
ILPA75JU-S105ST	1000 / 1050 / 1100mA	36 / 72 VDC	90%	80 / 88 VDC	75W
ILPA75JU-S070ST	665 / 700 / 735mA	54 / 108 VDC	91%	118 / 130 VDC	75W
ILPA75JU-S045ST	428 / 450 / 472mA	83 / 166 VDC	92%	195 / 215 VDC	75W
ILPA75JU-S035ST	332 / 350 / 368mA	107 / 214 VDC	92%	235 / 250 VDC	75W

### Electrical Characteristics

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Input Voltage	Operating Voltage	90		305	VAC
Input Frequency		47		63	Hz
Output Power Range	Vin=90 to 305VAC	0		75	W
Input Current (Low Line)	Io=Full load, Vin=115VAC			0.90	A
Input Current (High Line)	Io=Full load, Vin=230VAC			0.40	A
High Line Inrush Current	Io=Full load, 25°C, Cool start, Vin=230VAC			50	A
Power Factor Correction	Vin=110VAC		96	99	%
Efficiency	Io=Full Load, Vin=220VAC		88	92	%
Line Regulation	Io=Full Load			1	%
Load Regulation	Vin=230VAC			3	%
Over Voltage Protection	Latch mode. The power unit shall return to normal operation only after the power is turn-on again. (Please refer to output table.)				
Over Temperature Protection			110		°C
Short Circuit Protection	No damage shall occur when any output operating in a short circuit condition. The power supply shall be self-recovery when the fault condition is removed.				
Output Overshoot / Undershoot	When power on or off			10	%
Start Up Time	Io=Full Load, Vin=100VAC			0.6	S
Ripple & Noise (Peak to Peak)	Measured by 20 MHz bandwidth oscilloscope and the output paralleled a 0.1 uF ceramic capacitor and a 10 uF electrolytic capacitor.			5	% Vo

### Conditions

Parameter	Test Conditions	Min.	Typ.	Max.	Unit
Operating Temperature	Humidity: 10% RH to 100% RH	-35		70	°C
Storage Temperature	Humidity: 5% RH to 100% RH	-40		85	°C
MTBF: Operation temperature at 25°C, calculated per MIL-HDBK-217F		0.498M			Hours
Life Time at 25°C ambient temperature		0.065M			Hours

