

Customer Information Sheet

DRAWING No.: H3192-XX

SHEET 2 OF 2


IF IN DOUBT - ASK

(C)

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm

**SPECIFICATION:****MATERIAL:**

CONTACT SHELL - BRASS
CONTACT CLIP - BERYLLIUM COPPER

FINISH:

01 - 0.1 μ GOLD CLIP, 4 μ TIN SHELL
05 - 0.1 μ GOLD CLIP, 0.13 μ GOLD SHELL
46 - 1.3 μ 100% TIN CLIP, 4 μ TIN SHELL

ELECTRICAL:

CURRENT RATING AT 25°C = 2A MAX
CURRENT RATING AT 85°C = 1.75A MAX
CONTACT RESISTANCE (INITIAL) = 15 MILLIOHMS MAX
CONTACT RESISTANCE (AFTER CONDITIONING) = 25 MILLIOHMS MAX

MECHANICAL:

INSERTION FORCE (INITIAL) = 6N MAX, 2N MIN ($\varnothing 0.5$ mm GAUGE)
WITHDRAWAL FORCE (INITIAL) = 1.5N MIN, 0.5N MIN ($\varnothing 0.5$ mm GAUGE)
DURABILITY - 01, 05 = 500 OPERATIONS
46 = 50 OPERATIONS

ENVIRONMENTAL:

OPERATING TEMPERATURE = -55°C TO +125°C
FOR COMPLETE SPECIFICATION, SEE COMPONENT
SPECIFICATION C006XX (LATEST ISSUE).

ORDER CODE:**H3192-XX****FINISH:**

01 - GOLD CLIP, TIN SHELL
05 - GOLD CLIP, GOLD SHELL
46 - 100% TIN CLIP, TIN SHELL

NOTES:

1. RECOMMENDED PIN LENGTH = 2.40-2.30mm.
2. RECOMMENDED MOUNTING HOLE SIZE = $\varnothing 1.10$ -1.00mm.
3. RECOMMENDED PIN SIZE = $\varnothing 0.51$ - $\varnothing 0.46$ mm.

JMB 3 12.07.05 8627

NAME ISS. DATE C/NOTE

APPROVED:

CHECKED:

DRAWN: J CLAY

CUSTOMER REF.:

ASSEMBLY DRG:

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY
INFORMATION OR DESCRIPTIVE
MATTER SET OUT HEREON ARE
CONFIDENTIAL AND COPYRIGHT
PROPERTY OF THE HARWIN
GROUP AND MUST NOT BE
DISCLOSED, LOANED, COPIED
OR USED FOR MANUFACTURING,
TENDERING OR FOR ANY
OTHER PURPOSE WITHOUT
THEIR WRITTEN PERMISSION.

TOLERANCES

X. = ± 1 mm
X.X = ± 0.25 mm
X.XX = ± 0.10 mm
X.XXX = ± 0.01 mm
ANGLES = $\pm 5^\circ$
UNLESS STATED

MATERIAL:

SEE ABOVE

FINISH: SEE ABOVE

S/AREA:

mm²**TITLE:**

SUB-MINIATURE
SOCKET ASSEMBLY

DRAWING NUMBER:

H3192-XX

SHT
2
OF
2