

TOSHIBA

MICROWAVE SEMICONDUCTOR

TECHNICAL DATA

MICROWAVE POWER GaAs FET

TIM1112-4

FEATURES:

- HIGH POWER
P_{1dB} = 36.5 dBm at 11.7 GHz to 12.7 GHz
- BROAD BAND INTERNALLY MATCHED
- HIGH GAIN
G_{1dB} = 7.5 dB at 11.7 GHz to 12.7 GHz
- HERMETICALLY SEALED PACKAGE

RF PERFORMANCE SPECIFICATIONS (T_a = 25°C)

CHARACTERISTICS	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Output Power at 1 dB Compression Point	P _{1dB}	V _{DS} = 9 V f = 11.7 -12.7 GHz	dBm	35.5	36.5	-
Power Gain at 1 dB Compression Point	G _{1dB}		dB	6.5	7.5	-
Drain Current	I _{DS}		A	-	1.7	2.2
Power Added Efficiency	η _{add}		%	-	24	-
Channel-Temperature Rise	ΔT _{ch}	V _{DS} × I _{DS} × R _{th(c-c)}	°C	-	-	70

ELECTRICAL CHARACTERISTICS (T_a = 25°C)

CHARACTERISTICS	SYMBOL	CONDITION	UNIT	MIN.	TYP.	MAX.
Trans-conductance	g _m	V _{DS} = 3 V I _{DS} = 2.0 A	mS	-	1200	-
Pinch-off Voltage	V _{GSoff}	V _{DS} = 3 V I _{DS} = 60 mA	V	-2	-3.5	-5
Saturated Drain Current	I _{DSS}	V _{DS} = 3 V V _{GS} = 0 V	A	-	4.0	5.2
Gate-Source Breakdown Voltage	V _{GS0}	I _{GS} = -60 μA	V	-5	-	-
Thermal Resistance	R _{th(c-c)}	Channel to Case	°C/W	-	2.9	3.5

- * The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of TOSHIBA or others.
- * The information contained herein may be changed without prior notice. It is therefore advisable to contact TOSHIBA before proceeding with the design of equipment incorporating this product.




TIM1112-4

ABSOLUTE MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$)

CHARACTERISTIC	SYMBOL	UNIT	RATING
Drain-Source Voltage	V_{DS}	V	15
Gate-Source Voltage	V_{GS}	V	-5
Drain Current	I_{DS}	A	5.2
Total Power Dissipation ($T_c = 25^\circ\text{C}$)	P_T	W	30
Channel Temperature	T_{ch}	$^\circ\text{C}$	175
Storage Temperature	T_{stg}	$^\circ\text{C}$	-65-175

PACKAGE OUTLINE (2-9D1B)




HANDLING PRECAUTIONS FOR PACKAGED TYPE


Soldering iron should be grounded and the operating time should not exceed 10 seconds at 260°C .

RF PERFORMANCES

Output Power vs. Frequency




Output Power vs. Input Power



TIM1112-4


POWER DISSIPATION VS. CASE TEMPERATURE



TIM1112-4

TIM1112-4 S-PARAMETERS (MAGN. and ANGLES)

$V_{DS}=9V, I_{DS}=2A$



FREQUENCY (GHz)	S_{11}		S_{12}		S_{21}		S_{22}	
10.7	0.69	92	0.076	-121	2.20	-66	0.67	-143
10.9	0.65	74	0.095	-137	2.37	-83	0.64	-154
11.1	0.58	50	0.118	-161	2.59	-106	0.59	174
11.3	0.49	30	0.137	-179	2.78	-125	0.55	154
11.5	0.39	7	0.155	162	2.94	-145	0.50	132
11.7	0.24	-41	0.174	135	3.04	-173	0.40	102
11.9	0.17	-104	0.181	115	2.99	166	0.31	77
12.1	0.23	-166	0.185	95	2.84	145	0.21	49
12.3	0.35	153	0.180	71	2.63	120	0.13	-6
12.5	0.45	131	0.177	53	2.46	101	0.14	-63
12.7	0.53	112	0.170	35	2.25	83	0.19	-102
12.9	0.60	89	0.156	14	2.02	61	0.26	-130
13.1	0.63	73	0.145	-1	1.85	45	0.30	-143
13.3	0.66	57	0.138	-16	1.70	30	0.33	-153
13.5	0.69	36	0.127	-34	1.54	10	0.35	-164
13.7	0.70	21	0.118	-47	1.43	-6	0.36	-172