


CUT-OUT



	X	Y
0.75~1.25	13.6-0.18.7±0.1	
1.25~2.00	13.7-0.18.7±0.1	
2.00~3.00	13.8-0.18.7±0.1	

	A	W	R	B	■
柄颜色	灰色	白色	红色	黑色	柄颜色
底座颜色	A	W	R	B	●
	灰色	白色	红色	黑色	底座颜色

MATERIAL:

Cover:Nylon66, UL rated:94V-2 min
 Base:Nylon66, UL rated:94V-2 min
 Terminal:Brass,silver or tin plated
 Rating: 6A 125V AC (UL CUL)
 3A 250V AC (UL CUL VDE CE CQC)

Function:ON-OFF
 Contact Resistance: 50mΩ Max
 Insulation Resistance: 100MΩ Min
 Dielectric Strength: 2000VAC 1 minute
 Dielectrical life: 10,000 cycles
 Mechanical life :50,000 cycles
 Operating Temperature: -20℃~80℃
 Safety Approval:

公 差 TOLERANCES .X±0.3 .XX±0.15 角度 ANGLE±1° 单位 DIMENSION UNIT mm.

DASUNG 东莞市德松电子有限公司
 DASUNG (DONGGUAN) ELECTRONICS CO.,LTD

版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	核准 APPROVED BY	核对 CHECKED BY	日期 DATE	品名 TITLE	图号 DRAWING NO
A 2	整理图面	2016.05.04				2016.05.04	MR-5-110-C5N-BB	MR-5-110-C5N-BB_0
版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.	核准 APPROVED BY	核对 CHECKED BY	日期 DATE	品名 TITLE	图号 DRAWING NO