
## Compact air cylinder ADN-20-30-A-PPS-A Part number: 577170







## **Data sheet**

Feature	Value
Stroke	30 mm
Piston diameter	20 mm
Piston rod thread	M8
Type code	ADN
Cushioning	Self-adjusting pneumatic end-position cushioning
Mounting position	Any
Conforms to standard	ISO 21287
Piston rod end	External thread
Position sensing	For proximity sensor
Symbol	00991217
Variants	Piston rod at one end
Operating pressure	1.5 bar 10 bar
Mode of operation	Double-acting Double-acting
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Information on operating and pilot media	Operation with oil lubrication possible (required for further use)
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Ambient temperature	-20 °C 80 °C
Impact energy in the end positions	0.2 J
Cushioning length	3 mm
Theoretical force at 6 bar, retracting	141 N
Theoretical force at 6 bar, advancing	188 N
Moving mass at 0 mm stroke	30 g
Additional weight per 10 mm stroke	21 g
Basic weight with 0 mm stroke	131 g
Additional moving mass per 10 mm stroke	6 g
Type of mounting	With accessories Optionally: With internal thread With through-hole
Pneumatic connection	M5
Note on materials	RoHS-compliant
Cover material	Anodized Aluminum
Seals material	TPE-U(PUR)
Piston rod material	High-alloy steel
Material of cylinder barrel	Wrought aluminum alloy Smooth anodized