


# MB1005 thru MB1010 SERIES

## SINGLE-PHASE SILICON BRIDGE




**CHENG-YI  
ELECTRONIC**



### FEATURES

- UL recognized file #E149311
- Low forward voltage drop
- Surge overload rating-200 amperese peak
- Mounting position:Any
- Mounting:hole thru for #6 screw
- Electrically isolated base-1800Volts
- Weight:7.86 grams

VOLTAGE RANGE  
50 TO 1000 VOLTS  
CURRENT  
10.0 Amperes



Polarity shown on side of case;  
positive lead by beveled corner.

Dimensions in inches and (millimeters)

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.

#### MAXIMUM RATINGS (At $T_A=25^\circ\text{C}$ unless otherwise noted)

RATINGS		MB1005	MB101	MB102	MB104	MB106	MB108	MB1010	UNITS
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Bridge Input Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Output Current at:	@ $T_A=50^\circ\text{C}$	10.0							A
	@ $T_C=100^\circ\text{C}$	6.0							
	@ $T_A=50^\circ\text{C}$	6.0							
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	200							A
Operating Temperature Range	$T_J$	-55 to +125							$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 to +150							$^\circ\text{C}$

#### ELECTRICAL CHARACTERISTICS (At $T_A=25^\circ\text{C}$ unless otherwise noted)

CHARACTERISTICS		MB1005	MB101	MB102	MB104	MB106	MB108	MB1010	UNITS
Maximum Forward Voltage drop per element of 5.0A DC	$V_F$	1.1							V
Maximum Reverse Current at Rated DC Blocking Voltage per element	@ $T_A=25^\circ\text{C}$	5							$\mu\text{A}$
	@ $T_A=100^\circ\text{C}$	0.2							mA

# MB1005 thru MB1010 SERIES

## SINGLE-PHASE SILICON BRIDGE



**CHENG-YI  
ELECTRONIC**

### RATING AND CHARACTERISTICS CURVES MB1005 THRU MB1010 SERIES

Fig.1 - MAXIMUM NON-REPETITIVE  
FORWARD SURGE CURRENT




Fig.2 - TYPICAL FORWARD CURRENT  
DERATING CURVE




Fig.3 - TYPICAL INSTANTANEOUS FORWARD  
CHARACTERISTICS




Fig.4 - TYPICAL REVERSE CHARACTERISTICS

