



Series 811 Mighty Mouse High Density (HD) Rubber Protective Covers 809-190 and 809-191










These *splashproof molded rubber covers* fit all Series 811 plugs and receptacles. Braided black nylon lanyard is available with metal rings, cable tie or slipknot for attachment to panel or to cable. -40° to +120° C operating temperature, fungus resistant per MIL-STD-810G Method 508.6.

Materials	
Cover	Neoprene rubber blend, black
Lanyard	.062" (1.57) diameter nylon cord, black
Cable Tie	6/6 nylon, black, SST locking tab
Ring	Stainless steel, black zinc-cobalt finish
Crimp Sleeve	Copper Alloy, black zinc-cobalt finish

HOW TO ORDER

Sample Part Number

809-191	- 05	G	6	- SCS	C
Series	Shell Size	Lanyard Type	Lanyard Length	Attachment Code	Conductive Rubber
 <p style="text-align: center;">809-190 Protective Cover for use with Series 811 Receptacles</p>  <p style="text-align: center;">809-191 Protective Cover for use with Series 811 Plugs</p>	<p style="color: blue;">-05 -06 -07 -08 -09</p>	<p style="color: blue;">-G Nylon Rope (Omit for no lanyard)</p>	<p>Length in Inches</p>	 <p style="color: blue;">-WS Nylon Cable Tie, 1.77 Inch (45mm) Maximum Wire Bundle Diameter</p>	<p>Omit for Standard Neoprene</p> <p style="color: blue; text-align: center;">C Conductive Rubber</p>
				 <p style="color: blue;">-SCS Adjustable Slip Knot with Crimp Sleeve. The sleeve can be crimped with pliers for a permanent attachment.</p>	
				 <p style="color: blue;">-00 Lanyard With No Attachment (Fused End)</p>	
				Lug Terminals and Rings	
 <p>Lug Terminal</p>	<p style="color: blue;">-01 - .126 (3.20) I.D. -02 - .145 (3.68) I.D. -06 - .188 (4.78) I.D. -07 - .197 (5.00) I.D.</p>				
 <p>Solid Ring</p>	<p style="color: blue;">-08 - .385 (9.78) I.D. -09 - .445 (11.30) I.D. -10 - .516 (13.11) I.D. -11 - .570 (14.48) I.D. -12 - .583 (14.81) I.D. -13 - .635 (16.13) I.D. -14 - .695 (17.65) I.D. -15 - .776 (19.71) I.D. -16 - .885 (22.48) I.D. -17 - .896 (25.76) I.D. -18 - 1.015 (25.78) I.D. -19 - 1.070 (27.18) I.D. -20 - 1.135 (28.83) I.D. -21 - 1.141 (28.98) I.D.</p>				

Dimensions in Inches (millimeters) are subject to change without notice.