LP2500M0402AT LOW PASS FILTER SPECIFICATION

Rev. A


PRODUCT FEATURES

1. Surface mount low pass filter with a small size of 1.0 X 0.5 X 0.4 mm, RoHS compliant.
2. Provide low insertion loss and high rejection rate.
3. Highly stable under temperature and humidity changes.

RF CHARACTERISTICS


P/N LP2500M0402AT	Specification
Frequency range	2400-2500MHz
Insertion Loss (max)	0.45 dB at 25 °C 0.55 dB at -40°C to + 85°C
VSWR	1.7 max
Impedance	50 Ω
Attenuation (min.)	21 dB @ 4800- 5000MHz 21 dB @ 7200- 7500MHz
Operating temperature range	-40°C to +85°C

PHYSICAL DIMENSIONS




Symbol	Dimension (mm)
L	1.00 ± 0.10
W	0.50 ± 0.10
T	0.40 ± 0.10
A	0.35 ± 0.10
B, E	0.30 ± 0.10
C, D	0.15 ± 0.10

TERMINAL CONFIGURATION



PIN	Definition
P1	Input
P2	GND
P3	Output
P4	GND

PCB DESIGN/LAYOUT CONSIDERATION




Note:

- **Unit in mm**
- **Design trace width to be 50Ω impedance.**

667 E. Cochran St., Simi Valley, CA 93065
Phone: 1-805-522-9998, Fax: 1-805-522-9989

Typical RF Performance



FRONTIERUSA.COM © FRONTIERUSA.COM © FRONTIERUSA.COM © FRONTIERUSA.COM © FRONTIERUSA.COM ©