

Aluminum Electrolytic Capacitors Radial Miniature, Low Impedance





Fig. 1

QUICK REFERENCE DATA

DESCRIPTION	VALUE
Nominal case sizes (Ø D x L in mm)	10 x 12 to 18 x 40
Rated capacitance range, C _R	100 µF to 6800 µF
Tolerance on C _R	± 20 %
Rated voltage range, U _R	10 V to 63 V
Category temperature range	-40 °C to +105 °C
Endurance test at 105 °C	3000 h to 6000 h
Useful life at 105 °C	4000 h to 10 000 h
Useful life at 40 °C, 1.8 x I _R applied	200 000 h to 500 000 h
Shelf life at 0 V, 105 °C	1000 h
Based on sectional specification	IEC 60384-4 / EN130300
Climatic category IEC 60068	55 / 105 / 56

FEATURES

- Very long useful life: 4000 h to 10 000 h at 105 °C, high stability, high reliability
- Very low impedance and low ESR in smaller case sizes than the 150 RMI series
- Excellent ripple current capability
- AEC-Q200 qualified
- Polarized aluminum electrolytic capacitors, non-solid electrolyte
- Radial leads, cylindrical aluminum case with pressure relief, insulated with a blue sleeve
- Charge and discharge proof
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

AUTOMOTIVE
GRADE

RoHS
COMPLIANT

APPLICATIONS

- Power supplies (SMPS, DC/DC converters) for general industrial, EDP, audio-video, automotive, and telecommunications
- Smoothing, filtering, buffering

MARKING

The capacitors are marked (where possible) with the following information:

- Rated capacitance (in µF)
- Tolerance on rated capacitance, code letter in accordance with IEC 60062 (M for ± 20 %)
- Rated voltage (in V)
- Date code, in accordance with IEC 60062
- Code indicating factory of origin
- Name of manufacturer
- Upper category temperature (105 °C)
- Negative terminal identification
- Series number (170)

SELECTION CHART FOR C_R, U_R, AND RELEVANT NOMINAL CASE SIZES (Ø D x L in mm)

C _R (µF)	U _R (V)					
	10	16	25	35	50	63
100	-	-	-	-	-	10 x 12
150	-	-	-	-	10 x 12	10 x 16
220	-	-	-	-	10 x 16	10 x 20
	-	-	-	10 x 12	-	-
330	-	-	10 x 12	10 x 16	10 x 20	12.5 x 20
470	-	-	10 x 16	10 x 20	12.5 x 20	12.5 x 25
	-	10 x 12	-	-	-	16 x 20
680	10 x 12	10 x 16	10 x 20	12.5 x 20	12.5 x 25	16 x 20
	-	-	-	-	-	16 x 25
1000	10 x 16	10 x 20	12.5 x 20	12.5 x 25	16 x 25	16 x 31
	-	-	-	16 x 20	-	-
1200	-	-	-	-	16 x 31	-
1500	-	12.5 x 20	12.5 x 25	16 x 20	16 x 31	-
2200	12.5 x 20	12.5 x 25	16 x 20	16 x 31	-	18 x 40
3300	12.5 x 25	16 x 20	16 x 31	18 x 31	18 x 40	-
4700	16 x 25	16 x 31	16 x 35	18 x 40	-	-
6800	16 x 31	16 x 35	18 x 40	-	-	-
8200	-	18 x 40	-	-	-	-




DIMENSIONS in millimeters AND AVAILABLE FORMS

Fig. 2 - **Form CA:** Long leads

Fig. 3 - **Form CB:** Cut leads

Formed leads for $\varnothing D = 8$ mm with pitch $F = 5$ mm

Fig. 4 - **Form TFA:** Taped in box (ammopack)

Table 1

DIMENSIONS in millimeters, MASS AND PACKAGING QUANTITIES									
NOMINAL CASE SIZE $\varnothing D \times L$	CASE CODE	$\varnothing d$	$\varnothing D_{max.}$	$L_{max.}$	F	MASS (g)	PACKAGING QUANTITIES		
							FORM CA	FORM CB	FORM TFA
10 x 12	14	0.6	10.5	13.5	5.0 ± 0.5	≈ 1.6	1000	500	800
10 x 16	15	0.6	10.5	17.5	5.0 ± 0.5	≈ 1.9	500	500	800
10 x 20	16	0.6	10.5	22.0	5.0 ± 0.5	≈ 2.2	500	500	800
12.5 x 20	17	0.6	13.0	22.0	5.0 ± 0.5	≈ 4.0	500	500	500
12.5 x 25	18	0.6	13.0	27.0	5.0 ± 0.5	≈ 5.0	250	250	500
16 x 20	19a	0.8	16.5	22.0	7.5 ± 0.5	≈ 6.0	250	250	250
16 x 25	19	0.8	16.5	27.0	7.5 ± 0.5	≈ 8.0	250	250	250
16 x 31	20	0.8	16.5	33.5	7.5 ± 0.5	≈ 9.0	100	100	250
16 x 35	21	0.8	16.5	37.5	7.5 ± 0.5	≈ 11.0	100	100	-
18 x 31	1831	0.8	18.5	33.5	7.5 ± 0.5	≈ 12.5	100	100	-
18 x 40	1840	0.8	18.5	42.5	7.5 ± 0.5	≈ 16.5	100	100	-

ELECTRICAL DATA	
SYMBOL	DESCRIPTION
C_R	Rated capacitance at 100 Hz, tolerance $\pm 20\%$
I_R	Rated RMS ripple current at 100 kHz, 105 °C
I_{L2}	Max. leakage current after 2 min at U_R
$\tan \delta$	Max. dissipation factor at 100 Hz
Z	Max. impedance at 100 kHz

Note

- Unless otherwise specified, all electrical values in Table 2 apply at $T_{amb} = 20\text{ °C}$, $P = 86\text{ kPa}$ to 106 kPa , $RH = 45\%$ to 75%

Table 2

ELECTRICAL DATA AND ORDERING INFORMATION										
U_R (V)	C_R 100 Hz (μF)	NOMINAL CASE SIZE $\varnothing D \times L$ (mm)	I_R 100 kHz 105 °C (mA)	I_{L2} 2 min (μA)	$\tan \delta$ 100 Hz	Z 100 kHz +20 °C (Ω)	Z 100 kHz -40 °C (Ω)	ORDERING CODE MAL2170.....		
								BULK PACKAGING		TAPED
								FORM CA	FORM CB	FORM TFA
10	680	10 x 12	770	71	0.19	0.092	0.660	54681E3	64681E3	34681E3
	1000	10 x 16	1100	103	0.19	0.062	0.450	54102E3	64102E3	34102E3
	2200	12.5 x 20	1760	223	0.21	0.033	0.240	54222E3	64222E3	34222E3
	3300	12.5 x 25	2200	333	0.21	0.027	0.190	54332E3	64332E3	34332E3
	4700	16 x 25	2630	473	0.23	0.020	0.140	54472E3	64472E3	34472E3
	6800	16 x 31	3300	683	0.25	0.017	0.120	54682E3	64682E3	34682E3
16	470	10 x 12	770	78	0.16	0.092	0.660	55471E3	65471E3	35471E3
	680	10 x 16	1100	112	0.16	0.062	0.450	55681E3	65681E3	35681E3
	1000	10 x 20	1260	163	0.16	0.046	0.330	55102E3	65102E3	35102E3
	1500	12.5 x 20	1760	243	0.16	0.033	0.240	55152E3	65152E3	35152E3
	2200	12.5 x 25	2200	355	0.18	0.027	0.190	55222E3	65222E3	35222E3
	3300	16 x 20	2100	531	0.20	0.020	0.140	55332E3	65332E3	35332E3
	4700	16 x 31	3300	755	0.22	0.017	0.120	55472E3	65472E3	35472E3
	6800	16 x 35	3550	1091	0.24	0.017	0.120	55682E3	65682E3	-
25	8200	18 x 40	3800	1315	0.28	0.017	0.120	55822E3	65822E3	-
	330	10 x 12	770	86	0.14	0.092	0.660	56331E3	66331E3	36331E3
	470	10 x 16	1100	121	0.14	0.062	0.450	56471E3	66471E3	36471E3
	680	10 x 20	1260	173	0.14	0.046	0.330	56681E3	66681E3	36681E3
	1000	12.5 x 20	1760	253	0.14	0.033	0.240	56102E3	66102E3	36102E3
	1500	12.5 x 25	2200	378	0.14	0.027	0.190	56152E3	66152E3	36152E3
	2200	16 x 20	2100	553	0.16	0.020	0.140	56222E3	66222E3	36222E3
	3300	16 x 31	3300	828	0.16	0.017	0.120	56332E3	66332E3	36332E3
35	4700	16 x 35	3550	1178	0.18	0.017	0.120	56472E3	66472E3	-
	6800	18 x 40	3800	1703	0.22	0.017	0.120	56682E3	66682E3	-
	220	10 x 12	770	80	0.12	0.092	0.660	50221E3	60221E3	30221E3
	330	10 x 16	1100	118	0.12	0.062	0.450	50331E3	60331E3	30331E3
	470	10 x 20	1260	167	0.12	0.046	0.330	50471E3	60471E3	30471E3
	680	12.5 x 20	1760	241	0.12	0.033	0.240	50681E3	60681E3	30681E3
	1000	12.5 x 25	2200	353	0.12	0.027	0.190	50102E3	60102E3	30102E3
	1000	16 x 20	2100	353	0.12	0.020	0.140	90105E3	90106E3	90103E3
	1500	16 x 20	2100	528	0.12	0.020	0.140	50152E3	60152E3	30152E3
	2200	16 x 31	3300	773	0.14	0.017	0.120	50222E3	60222E3	30222E3
35	3300	18 x 31	3300	1155	0.16	0.017	0.120	50332E3	60332E3	-
	4700	18 x 40	3700	1648	0.18	0.017	0.120	50472E3	60472E3	-

ORDERING EXAMPLE

Electrolytic capacitor 170 series

470 μF / 16 V; $\pm 20\%$

Nominal case size: $\varnothing 10\text{ mm} \times 12\text{ mm}$; Form TFA

Ordering code: MAL217035471E3

ELECTRICAL DATA AND ORDERING INFORMATION

U_R (V)	C_R 100 Hz (μ F)	NOMINAL CASE SIZE $\varnothing$ D x L (mm)	I_R 100 kHz 105 °C (mA)	I_{L2} 2 min (μ A)	$\tan \delta$ 100 Hz	Z 100 kHz +20 °C (Ω)	Z 100 kHz -40 °C (Ω)	ORDERING CODE MAL2170.....		
								BULK PACKAGING		TAPED
								FORM CA	FORM CB	FORM TFA
50	150	10 x 12	560	78	0.10	0.155	1.300	51151E3	61151E3	31151E3
	220	10 x 16	900	113	0.10	0.114	0.820	51221E3	61221E3	31221E3
	330	10 x 20	1000	168	0.10	0.086	0.620	51331E3	61331E3	31331E3
	470	12.5 x 20	1320	238	0.10	0.059	0.420	51471E3	61471E3	31471E3
	680	12.5 x 25	1550	343	0.10	0.045	0.320	51681E3	61681E3	31681E3
	1000	16 x 25	2100	503	0.10	0.031	0.220	51102E3	61102E3	31102E3
	1200	16 x 31	2550	603	0.10	0.025	0.180	51122E3	61122E3	31122E3
	1500	16 x 31	2550	753	0.10	0.025	0.180	51152E3	61152E3	31152E3
63	3300	18 x 40	3380	1653	0.14	0.022	0.160	51332E3	61332E3	-
	100	10 x 12	445	66	0.10	0.260	1.860	58101E3	68101E3	38101E3
	150	10 x 16	615	97	0.10	0.181	1.290	58151E3	68151E3	38151E3
	220	10 x 20	770	141	0.10	0.140	1.010	58221E3	68221E3	38221E3
	330	12.5 x 20	1115	211	0.10	0.072	0.520	58331E3	68331E3	38331E3
	470	12.5 x 25	1320	299	0.10	0.064	0.460	58471E3	68471E3	38471E3
	470	16 x 20	1200	299	0.10	0.071	0.510	98475E3	98476E3	98473E3
	680	16 x 20	1200	431	0.10	0.071	0.510	58681E3	68681E3	38681E3
	680	16 x 25	1800	431	0.10	0.048	0.350	98685E3	98686E3	98683E3
	1000	16 x 31	2200	633	0.10	0.040	0.290	58102E3	68102E3	38102E3
	2200	18 x 40	3260	1389	0.12	0.031	0.220	58222E3	68222E3	-

ADDITIONAL ELECTRICAL DATA

PARAMETER	CONDITIONS	VALUE
Voltage		
Surge voltage		$U_s \leq 1.15 \times U_R$
Reverse voltage		$U_{rev} \leq 1 \text{ V}$
Current		
Leakage current	After 2 min at U_R	$I_{L2} \leq 0.01 C_R \times U_R + 3 \mu\text{A}$
Inductance		
Equivalent series inductance (ESL)	Case $\varnothing$ D ≤ 10 mm	Typ. 16 nH
	Case $\varnothing$ D ≥ 12.5 mm	Typ. 18 nH
Resistance		
Equivalent series resistance (ESR)	Calculated from $\tan \delta_{max}$ and C_R (see Table 2)	$ESR = \tan \delta / 2 \pi f C_R$


CAPACITANCE (C)


Fig. 5 - Typical multiplier of capacitance as a function of ambient temperature




Fig. 6 - Typical multiplier of capacitance as a function of frequency

EQUIVALENT SERIES RESISTANCE (ESR)




Fig. 7 - Typical multiplier of ESR as a function of ambient temperature




Fig. 8 - Typical multiplier of ESR as a function of frequency

IMPEDANCE (Z)




Fig. 9 - Typical multiplier of impedance as a function of ambient temperature




Fig. 10 - Typical impedance as a function of frequency




Fig. 11 - Typical impedance as a function of frequency

RIPPLE CURRENT AND USEFUL LIFE

Table 3

ENDURANCE TEST DURATION AND USEFUL LIFE			
NOMINAL CASE SIZE Ø D x L (mm)	CASE CODE	ENDURANCE AT 105 °C (h)	USEFUL LIFE AT 105 °C (h)
10 x 12	14	3000	4000
10 x 16	15	3000	6000
10 x 20	16	3000	6000
12.5 x 20	17	3000	7000
12.5 x 25	18	5000	8000
16 x 20	19a	3000	7000
16 x 25	19	5000	10 000
16 x 31	20	5000	10 000
16 x 35	21	5000	10 000
18 x 31	1831	6000	10 000
18 x 40	1840	8000	10 000

Note

- Multiplier of useful life code: CCC206




Fig. 12 - Multiplier of useful life as a function of ambient temperature and ripple current load

Table 4

MULTIPLIER OF RIPPLE CURRENT (I_R) AS A FUNCTION OF FREQUENCY							
NOMINAL CASE SIZE $\varnothing D \times L$ (mm)	FREQUENCY (Hz)						
	100	300	1000	3000	10 000	30 000	100 000
	I_R MULTIPLIER						
10 x 12	0.65	0.76	0.85	0.89	0.90	0.97	1.00
10 x 16	0.65	0.76	0.85	0.89	0.90	0.97	1.00
10 x 20	0.65	0.76	0.85	0.89	0.90	0.97	1.00
12.5 x 20	0.65	0.76	0.85	0.89	0.90	0.97	1.00
12.5 x 25	0.65	0.76	0.85	0.89	0.90	0.97	1.00
16 x 20	0.76	0.85	0.91	0.94	0.96	0.98	1.00
16 x 25	0.76	0.85	0.91	0.94	0.96	0.98	1.00
16 x 31	0.76	0.85	0.91	0.94	0.96	0.98	1.00
16 x 35	0.76	0.85	0.91	0.94	0.96	0.98	1.00
18 x 31	0.76	0.85	0.91	0.94	0.96	0.98	1.00
18 x 40	0.76	0.85	0.91	0.94	0.96	0.98	1.00

Table 5

TEST PROCEDURES AND REQUIREMENTS			
TEST		PROCEDURE (quick reference)	REQUIREMENTS
NAME OF TEST	REFERENCE		
Endurance	IEC 60384-4 / EN130300 subclause 4.13	$T_{amb} = 105\text{ }^{\circ}\text{C}$; U_R applied; for test duration see Table 3	$\Delta C/C: \pm 20\%$ $\tan \delta \leq 2 \times \text{spec. limit}$ $I_{L2} \leq \text{spec. limit}$
Useful life	CECC 30301 subclause 1.8.1	$T_{amb} = 105\text{ }^{\circ}\text{C}$; U_R and I_R applied; for test duration see Table 3	$\Delta C/C: \pm 30\%$ $\tan \delta \leq 3 \times \text{spec. limit}$ $I_{L2} \leq \text{spec. limit}$ no short or open circuit total failure percentage: $\leq 1\%$
Shelf life (storage at high temperature)	IEC 60384-4 / EN130300 subclause 4.17	$T_{amb} = 105\text{ }^{\circ}\text{C}$; no voltage applied; 1000 h after test: U_R to be applied for 30 min., 24 h to 48 h before measurement	$\Delta C/C: \pm 20\%$ $\tan \delta \leq 2 \times \text{spec. limit}$ $I_{L2} \leq \text{spec. limit}$

Statements about product lifetime are based on calculations and internal testing. They should only be interpreted as estimations. Also due to external factors, the lifetime in the field application may deviate from the calculated lifetime. In general, nothing stated herein shall be construed as a guarantee of durability.



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.