



RoHS Compliant

## Features

- Analog signal processing temperature compensated crystal oscillator
- Small package & Lower noises

## Standard frequency

- 14.31818MHz
- 17.734475MHz
- 28.63636MHz

## How to Order

TV 14.3181800 M □□□□□□  
 ①                      ②                      ③                      ④

- ① Function  
VC-TCXO → TV
- ② Output Frequency
- ③ Frequency Unit  
M→MHz
- ④ Individual Specification

Table 1

Model	Output waveform
VC-TCXO-155	clipped sinusoidal wave
VC-TCXO-155CB	CMOS

## Specifications

Item	Symbol	Conditions	Min.	Max.	Units
Frequency Range	fo	—	10	30	MHz
Frequency tolerance	fo-Tc	vs Temperature	-1.0	+1.0	×10 <sup>-6</sup>
	fo-Vcc	vs Voltage	-0.2	+0.2	×10 <sup>-6</sup>
Storage Temperature Range	T <sub>stg</sub>	—	-40	+85	°C
Operating Temperature Range	T <sub>use</sub>	—	-10	+60	°C
Supply Voltage	Vcc	—	4.75	5.25	V
Current consumption	Icc	VC-TCXO-155	—	3	mA
		VC-TCXO-155CB	—	20	mA
Frequency Aging	f <sub>age</sub>	1 year	1.0	1.0	×10 <sup>-6</sup>
Frequency Adjustment Range	f <sub>adjust</sub>	Internal Trimmer	-3.0	+3.0	×10 <sup>-6</sup>
Frequency Pull Range	f <sub>cont</sub>	—	-10	+10	×10 <sup>-6</sup>
Frequency Control Voltage	VC	—	0.5	4.5	V
Load	Load_R	VC-TCXO-155	10K	10K	ohm
	Load_C	VC-TCXO-155	10	10	pF
Output Level	Output Level	VC-TCXO-155	0.8	—	Vp-p
CMOS Load	L_CMOS	VC-TCXO-155CB	—	15	pF
Low Level Output Voltage	V <sub>OL</sub>	VC-TCXO-155CB	—	10% Vcc	V
High Level Output Voltage	V <sub>OH</sub>	VC-TCXO-155CB	90% Vcc	—	V
Symmetry	Symmetry	VC-TCXO-155CB, @50% Vcc	40	60	%

## Dimensions

(Unit: mm)

