

General Purpose Plastic Rectifiers

Reverse Voltage 50V to 1000V Forward Current 2.0 Amperes

RL201 thru RL207



Features

- Low cost
- Low leakage
- Low forward voltage drop
- High current capability
- The plastic material carries UL recognition 94V-0
- Tj is 150 °C (max) and Tstg is 175 °C (max) with PI glue

Mechanical Characteristics:

- Case: JEDEC DO-204AC(DO-15) molded plastic
- Terminals: Tin plated axial leads, solderable per MIL-STD-202E, method 208C
- Polarity: Color band denotes cathode
- Mounting position: Any
- Weight : 0.014oz., 0.39grams

Maximum Ratings and Electrical Characteristics

(Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%)

capacitive load, derate current by 20%)

Parameter	Symbol	Type							Units	
		RL201	RL202	RL203	RL204	RL205	RL206	RL207		
Maximum Repetitive peak reverse voltage	V _{RRM}	50	100	200	400	600	800	1000	V	
Maximum RMS voltage	V _{RMS}	35	70	140	280	420	560	700	V	
Maximum DC blocking voltage	V _{DC}	50	100	200	400	600	800	1000	V	
Maximum instantaneous forward voltage I _F =2A	V _F	1.1							V	
Maximum average forward rectified current, 0.375"(9.5mm) lead length at T _A =50°C	I _{F(AV)}	2							A	
Peak forward surge current @8.3ms single half sine wave superimposed on rated load (JEDEC method)	I _{FSM}	70							A	
Maximum DC reverse current at rated DC blocking voltage	T _A =25°C T _A =100°C	I _R	5							μA
			50							
Maximum full load reverse current full cycle Average @ .375"(9.5mm) lead length at T _L =75°C	I _{R(AV)}	30								
Typical junction capacitance (Note 1)	C _J	20							pF	
Typical Thermal Resistance	R _{θJA}	40							°C/W	
Storage temperature range	T _{stg}	-50 ~ +125							°C	
Operating junction temperature range	T _J	-50 ~ +150							°C	

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0VDC

Ratings and Characteristic Curves

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 3 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS






FIG. 5 - TYPICAL JUNCTION CAPACITANCE



DO-204AC(DO-15) Dimension



*:Typical

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	φ0.028	φ0.034	φ0.70	φ0.90	D	1.000	-	25.40	-
B	1.000	-	25.40	-	E	φ0.104	φ0.140	φ2.60	φ3.60
C	0.2300	0.3000	5.80	7.60					

Notes : 1.Controlling dimension : millimeters.

2.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.

3.If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.