
FAIRCHILD
SEMICONDUCTOR™

SUPER BRIGHT T-1 ¾ (5mm) LED LAMP – Water Clear

SUPER BLUE **MV8B01** **MV8B02**

PACKAGE DIMENSIONS



Note: 1) All dimensions are in inches (mm).
2) Lead spacing is measured where the leads emerge from the package.
3) Protruded resin under the flange is 1.5mm (0.059") max.

DESCRIPTION

These T-1 ¾ super-bright blue LEDs have a narrow viewing angle of 24° for concentrated light output. The blue diode chip is constructed with GaN/SiC technology and emits a peak wavelength of 430 nm.

FEATURES

- **Popular T-1 ¾ package**
- **Low drive current**
- **Solid state reliability**
- **Super high brightness**
- **Water clear optics**
- **Standard 100 mil. lead spacing**

ABSOLUTE MAXIMUM RATINGS (T_A=25°C unless otherwise specified)

DC Forward Current (I_F)	30 mA
Peak Forward Current (I_F) @ f = 1.0 KHz, Duty factor = 1/10	100 mA
Power Dissipation (P_d)	115 mW
Reversed Voltage (V_R) I_R = 10 µA	5
Operating Temperature Range	-40°C to +100°C
Storage Temperature Range	-40°C to +100°C
Lead Soldering Time	5 secs @ 260°C for wave solder; 10 secs @ 260°C for IR reflow

FAIRCHILD
SEMICONDUCTOR™

SUPER BRIGHT T-1 ¾ (5mm) LED LAMP – Water Clear

ELECTRO-OPTICAL CHARACTERISTICS (T_A=25°C unless otherwise specified)

Part Number:		MV8B01	MV8B02	Test Condition
Luminous Intensity (mcd)				I_F = 20 mA
	Minimum	400	630	
	Typical	600	940	
Forward Voltage (V_F)				I_F = 20 mA
	Typical	3.8	3.8	
	Maximum	4.5	4.5	
Peak Wavelength (nm)		430	430	I_F = 20 mA
Spectral Line Half Width (nm)		65	65	I_F = 20 mA
Viewing Angle (degrees)		24	24	I_F = 20 mA

TYPICAL ELECTRO-OPTICAL CHARACTERISTIC CURVES (T_A = 25°C)




Fig 1. Foward Current vs. Forward Voltage




Fig 2. Rel. Luminous Intensity vs. DC Forward Current




Fig 3. Rel. Intensity vs. Lead Temperature
(Pulsed 20 mA; 300 us pulse, 10 ms period)




Fig. 4 Rel. Intensity vs. Wavelength

FAIRCHILD
SEMICONDUCTOR™

SUPER BRIGHT T-1 ¾ (5mm) LED LAMP – Water Clear

TYPICAL ELECTRO-OPTICAL CHARACTERISTIC CURVES (T_A = 25°C)




Fig 5. Forward Current vs. Ambient Temperature




Fig. 6 Peak Forward Voltage vs. Forward Current (100 us test pulse, 1% duty cycle)




Fig. 7 Rel. Luminous Intensity vs. Peak Forward Current (300 us pulse width; 10 ms period)




Fig. 8 Pulse Derating Curve

FAIRCHILD
SEMICONDUCTOR™

SUPER BRIGHT T-1 3/4 (5mm) LED LAMP - Water Clear

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

© 2000 Fairchild Semiconductor Corporation